



A Moen Incorporated Brand

Model: CA40519 Series

Capstone®



One Handle Pullout Kitchen

DESCRIPTION

- Metal construction with various finishes identified by suffix
- 1/2" IPS connections
- Six (6) individual boxes per master carton
- Mounts in single hole or 3 hole installations
- Pullout spray with 59" metal hose

OPERATION

- Pivot action, lever style handle
- Temperature control by 90 degree arc
- Operates in stream or spray mode in the pullout or retracted position
- Will operate with less than 5 lbs. of torque

FLOW

- Flow limited to 1.5 gpm (5.7 L/min) at 60 psi

CARTRIDGE

- Ceramic disc technology
- Non-metallic, non-ferrous, and brass material
- Single body construction for easy replacement

STANDARDS

- Third party certified to IAPMO Green, CSA B-125.1, ASME A112.18.1, and all applicable requirements referenced therein including NSF61/9
- Meets CalGreen and Georgia SB370 requirements
- Contains no more than 0.25% weighted average lead content
- Complies with California Proposition 65 and the Federal Safe Water Drinking Act
- ADA for lever handles
- Features red/blue hot/cold temperature indicators

WARRANTY – RESIDENTIAL, COMMERCIAL

- Ten year limited warranty against defects in materials and manufacturing workmanship
- Refer to the installation instructions enclosed with each CFG product or call 1-888-450-4910 for complete warranty information

CRITICAL DIMENSIONS

- **Note:** This faucet is designed to be installed through 1 or 3 holes. 1-1/4" minimum diameter, 8" centers.
- Maximum deck thickness, 2-1/2" (64mm) for single hole mount; 1-5/8" (41mm) when 3 hole mounting studs are used.

