
Vane Rail (2" & 4")



Product Data Sheet





Features

Conforms to SMACNA spacing requirements. Refer to 2005 SMACNA-Figure 4-3. Holes provide for easy alignment Can be used with other vane systems Union Made Yellow Label

Description

Elgen's 2" & 4" Double Wall Turning Vane Rail is used in conjunction with Elgen's 2" & 4" Double Wall Turning Vane.
Elgen's 2" & 4" Double Wall Turning Vane Rail is used for securing and aligning Elgen's

is used for securing and aligning Elgen's 2" & 4" Turning Vanes. This process directs the airflow through rectangular elbows.

Standard Construction

Stamped using 22 GA ASTM A-653 G60/G90 Material 10' length

Size (in)	H (in)	S (in)
2	1-5/8	2-1/8
4	2	3-1/2

Optional Construction

Stainless Steel 304 Stainless Steel 316 Aluminum PCD Galvanneal (Paint Grip) Agion (Antimicrobial Coating)

Packaging

Size (in)	GA	Box Qty (ft)	Skid Qty (ft)	Weight (lbs)
2	22	200	7000	3100
4	22	100	3500	2300

Guarantee

All Elgen products are guaranteed by Elgen Manufacturing against defective material.

Elgen Manufacturing

10 Railroad Ave, Closter NJ 07624 Tel: 800.503.9805 :: Fax: 201.964.9030 info@elgenmfg.com :: www.elgenmfg.com