

# Low Lead Closet Supply Kits



## Product Features

- Low lead brass body
  - Low lead brass stem
  - cUPC approved
  - Certified to NSF 372 requirements
  - Flexible chrome plated copper risers with chrome plated steel deep flanges and chrome plated stops
- Operating pressure 125psi maximum
  - Operating temperature 40°F-160°F

## Model Numbers (\*For use copper tube only)

### Closet Supply

PFXCAC32CC12*	LF CP 5/8 comp X 3/8 comp clst sply kit
PFXCAZ32CC12	LF CP 1/2 NOM SWT angle clst sply kit
PFXCAT22CC12	LF CP 3/8 IPS X 3/8 comp clst sply kit
PFXCAS32CC12*	LF CP 1/2 SWT X 3/8 comp clst sply kit
PFXCAT22CLKC12	LF CP 3/8 IPS X 3/8 comp clst sply kit loose key
PFXCAC32CLKC12*	LF CP 5/8 comp X 3/8 comp clst sply kit loose key
PFXCAS32CLKC12*	LF CP 1/2 SWT X 3/8 comp clst sply kit loose key

### Heavy Duty Closet Supply

PFXHAT32CC12	LF CP 1/2 IPS X 3/8 comp clst sply kit
--------------	--



PFXCAC32CC12



PFXCAC32CLKC12

## Warranty and Codes

This PROFLO product carries a 1-year limited warranty. ASME A112.18.1-2005/CSA B125.1-05

