KOHLER_®

Features

- Vertically adjustable 3x magnifying mirror on inside of door.
- Three adjustable tempered glass shelves.
- Full-overlay mirrored door.
- Mirrored interior.
- Slow-close door prevents slamming.
- Two-way adjustable hinges with 108-degree opening capability for easy cabinet access.
- Can be installed with left- or right-hand swing.
- Includes mounting hardware for surface or recessed installation.
- Requires K-99012 side mirror kit (sold separately) for surface mount installation.

Material

• Anodized aluminum construction with a durable rust- and chip-resistant finish.

Required Accessories

K-99675 Medicine Cabinet Wood Side Kit

Optional Accessories

K-99012 Side Mirror Kit K-99662-24 Medicine Cabinet Surround K-99662-40 Medicine Cabinet Surround K-99661-15 Medicine Cabinet Surround K-99662-15 Medicine Cabinet Surround K-99663-15 Medicine Cabinet Surround



Codes/Standards

None Applicable

KOHLER[®] One-Year Limited Warranty


See website for detailed warranty information.




Verdera[®] Medicine Cabinet K-99001



Verdera® Medicine Cabinet K-99001





Technical Information

All product dimensions are nominal.

Recess-Mount Cutout:

Width:	13-1/2" (343 mm)
Height:	28-1/4" (718 mm)
Depth:	3-11/16" (94 mm)

Notes

Install this product according to the installation guide.

IMPORTANT! For recess mounting, the wall cavity must be framed and cabinet secured to framing studs. Reroute any electrical wires or water supply piping from the wall cavity. If you encounter drain or vent piping, or if your wall is load-bearing, consult a professional before proceeding.

For surface mounting, use anchors (not provided) rated for the loaded weight of this product. Refer to the anchor manufacturer's instructions.

When determining the height of the cabinet, ensure the mirrored door will clear all obstacles (such as a faucet). A minimum distance of 3" (76 mm) is required.

This cabinet is designed for either right or left door swing. Check for obstructions.

Cutout for recess-mount installations: 13-1/2"(343 mm) width x 28-1/4" (718 mm) height x 3-11/16" (94 mm) depth.

