THIS SPACE FOR DESIGNER/ENGINEER APPROVAL			
Job/Customer	Date	Contractor	
Model Specified	Qty	Approved By	
Designer/Engineer	Date	Contractor's PO#	
Submitted by	Date	Other	

## 8140 Series

Full Port Forged Brass Uni-Flange Ball Valve w/ Detachable Rotating Flange, Adjustable Packing Gland, Nuts & Bolts Press x Rotating Flange 250 CWP / 250°F Max ISO 9001





Item #	Size	CTN/CASE	A	В	C	D	E	F
81403HV	3⁄4"	1/20	3/4	3 5/16	2 1/4	2 3/8	3/8	3 3/16
81404HV	1"	1/20	1	4	2 5/8	2 3/8	3/8	3 3/16
81405HV	1 ¼"	1/20	1 1/4	4 7/16	2 15/16	3 3/8	3/8	3 3/16
81406HV	1 ½"	1/10	1 7/16	4 15/16	3 3/16	3 3/8	3/8	3 3/16
81407HV	2"	1/10	1 15/16	5 13/16	3 9/16	3 3/8	3/8	3 11/16

TEMP °F	PSI
100	250
250	200





**Specifications:** Designed for residential, commercial or industrial use with water only. This approved Webstone valve is actuated by a blowout proof stem and features an adjustable packing gland. HV models fit both standard and high velocity pumps.



Quality and Commitment Since 1954

www.webstonevalves.com · P: (800) 225-9529 · F: (800) 336-5133

Webstone product specifications in U.S. customary units are approximate and are provided for reference only. Webstone reserves the right to change or modify product design, construction, specifications or materials without prior notice and without incurring any obligation to make such changes and modifications on Webstone products previously or subsequently sold.

THIS SPACE FOR DESIGNER/ENGINEER APPROVAL			
Job/Customer	Date	Contractor	
Model Specified	Qty	Approved By	
Designer/Engineer	Date	Contractor's PO#	
Submitted by	Date	Other	



NO.	DESCRIPTION	MATERIAL
1	BODY	BRASS
2	END CAP	BRASS
3	BALL	BRASS CP
4	SEAT	PTFE
5	STEM	BRASS
6	PACKING GLAND	PTFE
7	PACKING NUT	BRASS
8	HANDLE	STEEL CP
9	HANDLE NUT	STAINLESS STEEL
10	ROTATING FLANGE RING	STAINLESS STEEL
11	ROTATING FLANGE	BRASS
12	FLANGE BOLTS	STAINLESS STEEL
13	FLANGE NUTS	STAINLESS STEEL



Quality and Commitment Since 1954

## www.webstonevalves.com · P: (800) 225-9529 · F: (800) 336-5133

Webstone product specifications in U.S. customary units are approximate and are provided for reference only. Webstone reserves the right to change or modify product design, construction, specifications or materials without prior notice and without incurring any obligation to make such changes and modifications on Webstone products previously or subsequently sold.