MOEN

Buy it for looks. Buy it for life.®

There is more than 1 version of this model. Page down to identify the version you have.

FAUCET DESCRIPTION

- Versatile, hands-free convenience in the kitchen Power Clean™ spray technology
- Allows users to control the faucet in 3 unique ways: Wave Sensor, Ready Sensor and familiar handle
- Powered by 6 AA batteries or optional AC adapter with power splitter
- Reflex™ pulldown system offers smooth operation, easy movement and secure docking
- Metal construction with various finishes identified by suffix
- Duralock[™] quick connect Pulldown spray with 68" braided hose
- Control box flexible supply lines with 3/8" compression fittings
- High arc spout provides height and reach to fill or clean large pots while pull down wand provides the maneuverability for cleaning or rinsing

OPERATION

- Lever style handle
- Temperature controlled by 100° arc of handle travel
- Operates with less than 5 lbs. of force
- Operates in stream or spray mode in the pulldown or retracted position Spout rotates 100 degrees

FLOW

Flow is limited to 1.5 gpm (5.7 L/min) at 60 psi

CARTRIDGE

1255[™] Duralast[™] cartridge

STANDARDS

- Third party certified to IAPMO Green, ASME A112.18.1/CSA B125.1 and all applicable requirements referenced therein including NSF 61/9G & 372 Meets CalGreen and Georgia SB370 requirements Complies with California Proposition 65 and with the Federal Safe Drinking Water Act

- The backflow protection system in the device consists of two independently operating check
- valves, a primary and a secondary which prevent backflow
- ADA 🔄 for lever handle

Wave

Sensor

Readv

Sensor

ì۵

WARRANTY

6-7/8"

(175mm)

1/2

(13mm)

Limited lifetime warranty against leaks, drips, finish defects to the original consumer purchaser

CRITICAL DIMENSIONS

(DO NOT SCALE)

- 5 year warranty electronic operation defects to the original consumer purchaser 5 year warranty against leaks, drips, finish defects if used in commercial installations
- 1 year warranty against electronic operation defects if used in commercial installations

Specifications



Brantford[™] with MotionSense[™] **Single Handle High Arc Pulldown Kitchen Faucet**

Models: 7185E series

NOTE: THIS FAUCET IS DESIGNED TO BE INSTALLED THROUGH 1 HOLE, 1-1/2" (38mm) MIN. DIA.



*motion*sense

1-21/32'

(42 mm)

7/8' (20mm)

29-3/8"

(746 mm)

Close up view of Control Box

4-1/8" (105 mm)

36["] (914mm)



2-5/8"

(67mm)