

# **ORBITAL FLARE**

The hilmor Orbital Flare was designed to produce quality flares – again and again. A tube-stop arrow allows precise positioning and placement so you can keep that nickel in your pocket. Plus, a clutch mechanism stops the flare to eliminate cracking the tube.



## Precise Flares, Every Time

An off-center mounted cone spins on an axis to effectively produce quality flares.



#### No Cracked Tubes

A clutch mechanism stops the flaring when the job is done.



### Simple Setup

A clothespin-inspired, spring-loaded block grips the tube securely.



#### Easy to Position

A tube-stop arrow slides to set correct height and positioning while ball detents allow for easy flaring cone alignment.

## **Product Specifications**

Item Number	1838952
Product Description	FTO
Tube Sizes (O.D.)	3/16", 1/4", 5/16", 3/8", 1/2", 5/8", 3/4"
Dimensions	
Length Width Height Weight	8-1/2" 4-5/8" 5-1/4" 3.8 lbs.
Tube Materials	Soft Tubing Only Copper, Steel, Aluminum, Brass
Flare Type	45 degree
Flare Type	Copper, Steel, Aluminum, Brass

mait

A clutch mechanism stops the flare when the job is done to eliminate cracking the tube.



An off-center mounted cone helps to uniformly shape the tube.

35