


BULKHEAD FEMALE CONNECTOR 774 LF	60	
BULKHEAD REDUCER 774 LT	60	
BULKHEAD MALE CONNECTOR 774 LM	61	
BULKHEAD REDUCING UNION 775 L	62	
UNION CROSS 7102 L	63	
CAP 7108 L	64	
PLUG 7121 L	65	
FEMALE ADAPTER TUBE TO PIPE 739 LF	66	
MALE ADAPTER TUBE TO PIPE 739 LM	68	
MALE ADAPTER TUBE TO PIPE 739 LMR	70	
MALE ADAPTER TUBE TO PIPE 739 LMG	71	
WELD ADAPTER TUBE TO PIPE 739 LN	72	
SOCKET WELD ADAPTER 739 LW	72	
MALE ADAPTER 739 LMOB	73	
LET-LOK® TO AN ADAPTER 761 LFL	74	
LET-LOK® TO AN UNION 762 LFL	74	
LET-LOK® TO AN BULKHEAD UNION 774 LFL	74	
MALE ADAPTER TUBE TO AN 739 LTFL	75	
PARALLEL THREADS SEALING	76	
MALE NUT 961 L	78	
UNION 962 L	78	
REDUCING UNION 963 L	78	
UNION TEE 964 L	78	
POSITIONABLES	79	
UNION DIELECTRIC 762 L Dielectric	86	
MALE CONNECTOR 768 LC	88	
ALLOY 400 CONNECTOR	89	
ALLOY C-276 CONNECTOR	91	
SUPER DUPLEX 2507 CONNECTOR	95	
ACCESSORIES	95	
STOP COLLAR	99	

LET-LOK® MATERIAL DESCRIPTION

EXAMPLE: 768L



Material Description

1/4

X

1/4

764 L UNION TEE



ALL TUBE (METRIC)

Ordering Information	A Tube O.D.	D		W Wrench Flat		N		E		I	
	mm	mm	mm	inch	mm	mm	mm	mm	mm	mm	mm
764L _ 2	2	1.7		3/8	9.5	15.7		22.3		12.9	
764L _ 3	3	2.4		3/8	9.5	15.7		22.3		12.9	
764L _ 4	4	2.4		1/2	12.7	18.8		25.4		13.7	
764L _ 6	6	4.8		1/2	12.7	19.6		27.0		15.3	
764L _ 8	8	6.4		5/8	15.9	22.4		29.9		16.2	
764L _ 10	10	7.9		11/16	17.5	23.9		31.5		17.2	
764L _ 12	12	9.5		13/16	20.6	25.9		36.0		22.8	
764L _ 14	14	11.1		15/16	23.8	28.7		38.8		24.4	
764L _ 15	15	11.9		15/16	23.8	28.7		38.8		24.4	
764L _ 16	16	12.7		15/16	23.8	28.7		38.8		24.4	
764L _ 18	18	15.1		1 1/16	27.0	29.7		39.8		24.4	
764L _ 20	20	15.9		1 3/8	34.9	34.5		44.6		26.0	
764L _ 22	22	18.3		1 3/8	34.9	34.5		44.6		26.0	
764L _ 25	25	21.8		1 3/8	34.9	36.8		49.1		31.3	
764L _ 38	*38	33.7		-	55.0	56.4		84.0		49.4	
764L _ 50	*50	45.2		2 3/4	69.9	68.9		106.0		65.0	

ALL TUBE (INCH)

Ordering Information	A Tube O.D.		D		W Wrench Flat		N		E		I	
	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
764L _ 1/16	1/16	1.58	.05	1.27	3/8	9.5	.55	14.00	.70	17.80	.34	8.6
764L _ 1/8	1/8	3.17	.09	2.28	3/8	9.5	.62	15.74	.88	22.35	.50	12.7
764L _ 3/16	3/16	4.76	.12	3.04	1/2	12.7	.70	17.80	.96	24.40	.54	13.7
764L _ 1/4	1/4	6.35	.19	4.82	1/2	12.7	.77	19.55	1.06	26.90	.60	15.2
764L _ 5/16	5/16	7.93	.25	6.35	5/8	15.9	.88	22.35	1.17	29.71	.64	16.2
764L _ 3/8	3/8	9.52	.28	7.11	5/8	15.9	.91	23.11	1.20	30.48	.66	16.8
764L _ 1/2	1/2	12.70	.41	10.41	13/16	20.6	1.02	25.90	1.42	36.06	.90	22.9
764L _ 5/8	5/8	15.87	.50	12.70	15/16	23.8	1.13	28.70	1.53	38.90	.96	24.4
764L _ 3/4	3/4	19.05	.62	15.74	1 1/16	27.0	1.17	29.70	1.57	39.90	.96	24.4
764L _ 7/8	7/8	22.22	.72	18.29	1 3/8	34.9	1.36	34.54	1.76	44.70	1.02	25.9
764L _ 1	1	25.40	.88	22.35	1 3/8	34.9	1.45	36.83	1.93	49.00	1.23	31.2
764L _ 1 1/4	*1 1/4	31.75	1.09	27.7	1 11/16	42.9	1.75	44.50	2.62	66.55	1.62	41.2
764L _ 1 1/2	*1 1/2	38.10	1.34	34.0	2	50.8	2.00	50.80	3.07	77.98	1.97	50.0
764L _ 2	*2	50.80	1.81	45.97	2 3/4	69.9	2.75	69.85	4.22	107.19	2.66	67.6

* Including low friction paste, see page 91

"D" - Dimension is minimum opening. Dimensions are for reference only, and are subject to change without notice.