

## Female X Female Swivel Connection

### Description

The single outlet open snoot is constructed of cast brass\*. The single swivel is complete with gasket and comes standard with pin lugs. Configured with FNPT x FNST swivel. (Plug with chain and breakable caps. Sold Separately)



### Installation

Installation can be achieved with tools readily available in the field using common installation practices. Make sure male threads of pipe to which the snoot is being attached are liberally coated with a pipe thread sealant such as PipeFit Thread Sealant with PTFE or PTFE Thread Sealant Tape. Tighten the snoot until hand tight. Tighten one additional turn past hand tight to achieve a water tight seal of the threads. **DO NOT OVER TIGHTEN! Over Tightening may cause thread failure as well as cracking of the snoot body.**

### Specifications


**Material:**  
B16 Brass\*

**CAUTION:**  
1½ FNPT x FNST  
1½ FNPT x 2½ FNST\*  
2 FNPT x 2½ FNST\*  
2½ FNPT x FNST\*  
3 FNPT x 2½ FNST\*  
3 FNPT x 3 FNST

**\*Swivels:**

NST	3.0686 x 7½ TPI
BCT	3.0000 x 8 TPI
CF	2.9900 x 7½ TPI
CIN-new	3.0580 x 6 TPI
CIN-old	3.0930 x 6 TPI
CLV	3.0780 x 8 TPI
Dayton	3.2340 x 6 TPI
DET	3.1250 x 7½ TPI
NovaSco	3.2300 x 5 TPI
NYFD	3.0300 x 8 TPI
ONT	3.1250 x 5 TPI
PHX	3.0620 x 6 TPI
QST	3.0310 x 7 TPI
Raleigh	3.3400 x 6 TPI
Richmon	3.3120 x 8 TPI
TEM	3.0750 x 6 TPI

\*Contains lead. Not for use in water systems intended for human consumption.



3198 LIONSHEAD AVE  
CARLSBAD, CA 92010  
TEL + 1 760 599-1168  
+ 1 800 344-1822  
FAX + 1 800 344-3775