



A Moen Incorporated Brand




## Pressure Balancing Cycling In-Wall Valve

### DESCRIPTION

- Brass construction
- 1/2" connections: IPS - exterior CC - interior
- Pressure balancing 4 port cycling valve
- Inlets - 1/2" PEX adaptors, 90° elbow, pointing down
- Shower outlet - 1/2" PEX adaptor, straight
- Tub outlet - 8" x 7" copper hole
- Valve comes completely assembled with nose cone, cartridge and plaster ground
- Twelve (12) individual boxes per master carton

### OPERATION

- Pressure balancing mechanism maintains selected discharge temperature to  $\pm 3.6^{\circ}\text{F}$
- For use in wall thicknesses 2.5" or greater

### CARTRIDGE

- European ceramic disc technology
- Non-metallic, non-ferrous, and plastic material

### STANDARDS

- Third party certified to ASME A112.18.1/CSA B125.1, ASSE 1016, and all applicable requirements referenced therein, California Proposition 65, Illinois, Massachusetts, and Texas

### WARRANTY – RESIDENTIAL, COMMERCIAL

- Ten year limited warranty against defects in materials and manufacturing workmanship
- Refer to the installation instructions enclosed with each CFG product or call 1-888-450-4910 for complete warranty information