


Features

- Acrylic
- Freestanding bath
- Two-piece design
- Fluted apron
- Integral molded lumbar supports at both ends for comfort
- Center drain
- Textured bottom surface
- 72" (1829 mm) x 36" (914 mm) x 25-3/4" (654 mm)

Codes/Standards Applicable

Specified model meets or exceeds the following:

• CSA B45.5/IAPMO Z124



STARGAZETM

FLUTED APRON

FREESTANDING BATH WITH

Colors/Finishes

- 0: White
- 96: Biscuit

Accessories

- CP: Polished Chrome
- Other: Refer to Price Book for additional colors/finishes

Specified Model

Model	Description	Colors/Finishes	
K-6367	Freestanding bath with fluted apron	0 🗆	96
Recommer	nded Accessories		
K-7265	Toe-tap bath drain - with brass tee and pipe OR	🗆 CP	Other
K-37385	PVC cable bath drain - less tee and pipe		🗆 NA
-	Frim (for K-37385 Cable Bath Drain Only)		
K-T37391	Cable bath drain trim - Basic Rotary OR		□ Other
-			Other Other
K-T37391	Cable bath drain trim - Basic Rotary OR		
K-T37391 K-T37392	Cable bath drain trim - Basic Rotary OR Cable bath drain trim - Contemporary Rotary OR		Other
K-T37391 K-T37392 K-T37393	Cable bath drain trim - Basic Rotary OR Cable bath drain trim - Contemporary Rotary OR Cable bath drain trim - Traditional Rotary OR		Other Other
K-T37391 K-T37392 K-T37393 K-T37394	Cable bath drain trim - Basic Rotary OR Cable bath drain trim - Contemporary Rotary OR Cable bath drain trim - Traditional Rotary OR Cable bath drain trim - Victorian Rotary OR		Other Other Other Other

Product Specification

The freestanding bath shall be made of acrylic. Bath shall be 72" (1829 mm) in length, 36" (914 mm) in width, and 25-3/4" (654 mm) in height. Bath shall be two-piece design and includes fluted apron. Bath features integral molded lumbar supports at both ends for comfort. Bath shall have a center drain and features textured bottom surface. Freestanding bath shall be Kohler Model K-6367-_____.

STARGAZETM

Technical Information

Fixtu	Fixture*:				
Bath	Bathing well:				
Basi botto	in area, om	24-1/2" (622 mm) x 50" (1270 mm)			
Basi	in area, top	27-1/2" (699 mm) x 61" (1549 mm)			
Weig	ght	152 lbs (68.9 kg)			
Тоо	To overflow:				
Wat	er depth	17″ (432 mm)			
Cap	acity	90 gal (341 L)			
* Ap	* Approximate measurements for comparison only.				

Installation Notes

Install this product according to the installation guide.

CAUTION: Risk of personal injury. Obtain sufficient help to carefully lift or move the bath.

This bath is designed for freestanding installation only.

Do not support the load weight of the bath by the rim.

Floor support under bath must provide for a minimum of 80 Ibs/square foot (390.6 kg/square meter) loading.

Hot water supply should be 70% of capacity or greater. Installations will vary.

If installing a rim-mount faucet, make sure there is no interference with the drain overflow before drilling any holes. Consult local and national codes for minimum air gap requirements if installing a spout on the faucet deck.

No change in measurements if connected with drain illustrated. (K-7265)

1214186-4-D

