



Low Lead Quarter Turn Supply Stops

Product Features

- Chrome plated stops
- Low lead brass body
- Low lead brass stem
- Low lead brass ball mechanism
- Angle, straight, and 3-way stops available
- cUPC approved
- Certified to NSF 372 requirements
- Operating pressure 125psi maximum
- Operating temperature 40°F-160°F
- Quarter turn operation

Model Numbers (*For use on copper tubing only)

Angle Stops

- PFXQAC31C* LF CP 5/8 OD X 1/4 OD QT ANG VLV
 PFXQAC32C* LF CP 5/8 OD X 3/8 OD QT ANG VLV
 PFXQAP32C LF CP 1/2 PEX X 3/8 OD QT ANG VLV
 PFXQAS32C* LF CP 1/2 SWT X 3/8 OD QT ANG VLV
 PFXQAT22C LF CP 3/8 FIP X 3/8 OD QT ANG VLV
 PFXQAT32C LF CP 1/2 FIP X 3/8 OD QT ANG VLV
 PFXQAV32C LF CP 1/2 CPVC X 3/8 OD QT ANG VLV
 PFXQAC32CLK* LF CP 5/8 OD COMP X 3/8 COMP QT ANG ST LK VLV
 PFXQAJ34C LF CP 5/8 OD X 7/16 & 1/2 SJ QT ANG ST VLV

Straight Stops

- PFXQSC32C* LF CP 5/8 OD X 3/8 OD QT STRT VLV
 PFXQSF22C LF CP 3/8 FEM COMP X 3/8 OD QT STRT VLV
 PFXQSP32C LF CP 1/2 PEX X 3/8 OD QT STRT VLV
 PFXQSS32C* LF CP 1/2 SWT X 3/8 OD QT STRT VLV
 PFXQST22C LF CP 3/8 FIP X 3/8 OD QT STRT VLV
 PFXQST32C LF CP 1/2 FIP X 3/8 OD QT STRT VLV
 PFXQSV32C LF CP 1/2 CPVC X 3/8 OD QT STRT VLV

3-Way Stops

- PFXQ3C322C* LF CP 5/8 X 3/8 X 3/8 QT 3 WAY VLV



PFXQAT32C



PFXQAC32C



PFXQSC32C

Warranty and Codes

This PROFLO product carries a 1-year limited warranty. ASME A112.18.1-2005/CSA B125.1-05

