NW2000CA-LED

4" 2000 Series - Evolution LED

IC Air Tight New Construction Housing for PAR16 LED and PAR20 LED Lamp

Project Notes Fixture Type Date

SPECIFICATIONS

HOUSING DETAILS

18 gauge 0.051" (1.3 mm) thickness galvanized steel.

Approved for installation in insulated ceiling with direct contact to insulating material (except polyurethane).

Air Tight.

Junction box can support up to 10 – 14 gauge wires or

8 – 12 gauge wires.

Below-ceiling accessible.

Removable socket enabling use of PAR16 LED or PAR20 LED into adjustable trims. (See installation instructions for more details)

MOUNTING Cutout diameter: Ø 4-1/4" (108 mm)

Can fit in ceilings up to 1-1/2" (38 mm) thick.

Requires a 5-1/4" (134 mm) clearance beyond the ceiling level. Contrast hooks for ease of installation and a perfect fit to ceiling. Mounting bars extend from 10" (254 mm) to 24-1/2" (622 mm) to fit in most ceilling structures (compatible with suspended ceilings). No light leakage.

LAMP PAR16 LED 8W MAX PAR20 LED 10W MAX

This product was designed for PAR16 or PAR20 LED lamp. If you want to use a dimmer, please refer regularly to the lamp manufacturer dimmer compatibility list.

VOLTAGE 120 Volts

COMPATIBLE	PAR16 LED		PAR20 LED	
TRIMS	R2000	R2450VT	A2000	A2450S
	R2000DG	S2000	A2000V	A2450VT
	R2000V	S2100	A2000VL	A2451S
	R2051	T2000	A2100	D2000
	R2100		A2400S	D2100
	R2100VT		A2401S	


THERMAL PROTECTION TC 212°F (100°C)


CERTIFICATION • cULus **E343977** for damp locations

• Certified Air Tight ASTM E283

5 years on socket and 1 year on other components.









WARRANTY







1009, rue du Parc Industriel Lévis (Québec) G6Z 1C5 Canada

Tel.: 1-888-839-4624 Fax: 1-877-839-7057 info@contrastlighting.com


info@contrastlighting.com www.contrastlighting.com © 2015 Contrast Lighting M.L. Inc. All rights reserved

Contrast Lighting reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.

NW2000CA-LED

4" 2000 Series - Evolution LED

CODIFICATION EXAMPLE



CODE DE COMMANDE

MODEL		SERIES			SOURCE		
NW		2000			CA-LED		
NW	New Construction	2000	4" Series	CA-L	.ED	PAR16 LED Lamp or PAR20 LED Lamp	









1009, rue du Parc Industriel© 2015Lévis (Québec) G6Z 1C5 CanadaAll right:

Tel.: 1-888-839-4624 Fax: 1-877-839-7057 info@contrastlighting.com

www.contrastlighting.com

© 2015 Contrast Lighting M.L. Inc. All rights reserved

Contrast Lighting reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.