


## TORQUESAFE™ SPRINKLER HEAD TEE Gasket Sealed Brass Thread Insert Style

Socket x Gasket FIPT x Socket

With Elastomer Seal - Use NO Thread Sealant




| Part Number | Size    | G     | G1    | G2      | H       | H1      | H2    | L       | M     | M1    | M2    | Approx. Wt. (Lbs.) |
|-------------|---------|-------|-------|---------|---------|---------|-------|---------|-------|-------|-------|--------------------|
| 4203-122 G  | 1x1/2x1 | 19/32 | 13/16 | 1-13/32 | 1-19/32 | 1-27/32 | 1-3/4 | 3-11/32 | 1-5/8 | 1-5/8 | 1-3/8 | .25                |

Not intended to convey or dispense water for human consumption through drinking or cooking

## SPRINKLER HEAD TEE Brass Thread Insert Style

Socket x FIPT x Socket




| Part Number | Size    | G     | G1  | G2    | H     | H1    | H2      | L     | M       | M1      | M2     | Approx. Wt. (Lbs.) |
|-------------|---------|-------|-----|-------|-------|-------|---------|-------|---------|---------|--------|--------------------|
| 4203-122    | 1x1/2x1 | 23/32 | 3/4 | 1-1/4 | 1-5/8 | 1-5/8 | 1-15/16 | 3-1/2 | 1-23/32 | 1-23/32 | 1-3/16 | .25                |

Not intended to convey or dispense water for human consumption through drinking or cooking

## SPRINKLER HEAD TEE Special Reinforced Plastic Thread Style

Socket x SR FIPT x Socket



| Part Number | Size    | G     | G1    | G2     | H       | H1    | H2      | L       | M     | M1    | M2     | Approx. Wt. (Lbs.) |
|-------------|---------|-------|-------|--------|---------|-------|---------|---------|-------|-------|--------|--------------------|
| 4203-122SR  | 1x1/2x1 | 27/32 | 23/32 | 1-3/32 | 1-23/32 | 1-5/8 | 1-25/32 | 3-13/32 | 1-3/4 | 1-3/4 | 1-3/16 | .21                |