


## REDUCING TEE

Socket x Socket x Socket

(continued)



| Part Number | Size              | G       | G1      | G2      | H       | H1      | H2      | L       | M       | M1      | M2      | Approx. Wt. (Lbs.) |
|-------------|-------------------|---------|---------|---------|---------|---------|---------|---------|---------|---------|---------|--------------------|
| 4201-291    | 2-1/2x2-1/2x1-1/2 | 1-3/16  | 1/2     | 1-3/16  | 2-15/16 | 1-7/8   | 2-15/16 | 5-7/8   | 3-15/32 | 2-11/32 | 3-15/32 | 1.26               |
| 4201-292    | 2-1/2x2-1/2x2     | 1-13/32 | 1-5/8   | 1-13/32 | 3-3/16  | 3-1/8   | 3-3/16  | 6-11/32 | 3-1/2   | 3-7/8   | 3-1/2   | 1.34               |
| 4201-335    | 3x3x1             | 7/8     | 1-15/16 | 7/8     | 2-3/4   | 3-1/16  | 2-3/4   | 5-15/32 | 4-3/16  | 1-23/32 | 4-3/16  | 1.26               |
| 4201-336*   | 3x3x1-1/4         | 1-3/8   | 1-3/4   | 1-3/8   | 3-5/16  | 3-1/2   | 3-5/16  | 6-5/8   | 4-1/8   | 2-7/8   | 4-1/8   | 1.94               |
| 4201-337    | 3x3x1-1/2         | 1-5/32  | 2-1/16  | 1-5/32  | 3-1/32  | 3-7/16  | 3-1/32  | 6-3/32  | 4-3/16  | 2-3/8   | 4-3/16  | 1.46               |
| 4201-338    | 3x3x2             | 1-7/16  | 1-13/16 | 1-7/16  | 3-5/16  | 3-5/16  | 3-5/16  | 6-19/32 | 4-3/16  | 2-7/8   | 4-3/16  | 1.69               |
| 4201-339    | 3x3x2-1/2         | 1-3/4   | 1-31/32 | 1-3/4   | 3-5/8   | 3-23/32 | 3-5/8   | 7-1/4   | 4-3/16  | 3-17/32 | 4-3/16  | 2.11               |


\* Branch Outlet Sized with Bushing

## TorqueSafe™ SPRINKLER HEAD TEE

Gasket Sealed Brass  
Thread Insert Style

Socket x Socket x Gasket FIPT

With Elastomer Seal - Use NO Thread Sealant




| Part Number | Size            | G    | G1      | G2   | H       | H1      | H2      | L       | M       | M1    | M2      | Approx. Wt. (Lbs.) |
|-------------|-----------------|------|---------|------|---------|---------|---------|---------|---------|-------|---------|--------------------|
| 4202-101 G  | 3/4x3/4x1/2     | 7/16 | 1-3/16  | 7/16 | 1-7/16  | 1-7/16  | 1-17/32 | 2-29/32 | 1-3/8   | 1-3/8 | 1-3/8   | .22                |
| 4202-124 G  | 1x3/4x1/2       | 7/16 | 1-11/32 | 9/16 | 1-9/16  | 1-11/16 | 1-9/16  | 3-1/8   | 1-11/16 | 1-3/8 | 1-3/8   | .26                |
| 4202-130 G  | 1x1x1/2         | 7/16 | 1-11/32 | 7/16 | 1-9/16  | 1-11/16 | 1-9/16  | 3-1/8   | 1-23/32 | 1-3/8 | 1-23/32 | .28                |
| 4202-166 G  | 1-1/4x1-1/4x1/2 | 7/16 | 1-5/8   | 7/16 | 1-11/16 | 1-15/16 | 1-11/16 | 3-3/8   | 2-1/16  | 1-3/8 | 2-1/16  | .34                |
| 4202-209 G  | 1-1/2x1-1/2x1/2 | 1/2  | 1-13/16 | 1/2  | 1-7/8   | 2-3/32  | 1-7/8   | 3-3/4   | 2-11/32 | 1-3/8 | 2-11/32 | .41                |
| 4202-247 G  | 2x2x1/2         | 1/2  | 2-1/16  | 1/2  | 2       | 2-11/32 | 2       | 4-1/32  | 2-27/32 | 1-3/8 | 2-27/32 | .54                |

Not intended to convey or dispense water for human consumption through drinking or cooking

## SPRINKLER HEAD TEE

Brass Thread Insert Style

Socket x Socket x Fipt



| Part Number | Size  | G     | G1     | G2    | H       | H1      | H2      | L       | M       | M1      | M2      | Approx. Wt. (Lbs.) |
|-------------|-------|-------|--------|-------|---------|---------|---------|---------|---------|---------|---------|--------------------|
| 4202-010    | 1x1x1 | 21/31 | 1-3/16 | 21/31 | 1-25/32 | 1-29/32 | 1-25/32 | 3-19/32 | 1-23/32 | 1-23/32 | 1-23/32 | .37                |

Not intended to convey or dispense water for human consumption through drinking or cooking