

Sight Glass



Description

Fire Protection Products' Sight Glass are cast from high quality brass* alloy. This assures lasting performance and serviceability. Available in both "full flow" and "restricted orifice" design.

Flow can be viewed through two high impact Lexan (polycarbonate) windows on either side of the sight glass. All models feature male by female thread patterns for easy "in line" installation. The "full flow" design is suitable for system flow verification. The restricted orifice types can be used to simulate system sprinkler head flow which can be viewed through either window.

Installation

Installation can be made using readily available field tools and materials. Apply a suitable pipe thread sealant to the either the male or female threads. The brass sight glass with the restricted orifice must be installed so the direction of flow is from the female thread to the male thread. This allows the restricted stream to be viewed through the Lexan (polycarbonate) windows. The unrestricted models may be

installed in either direction, however, they should be installed consistent with industry standards.

The sight glass threads have been machined according to standard iron pipe thread specifications. Installation is similar to other threaded fittings. **Caution: Do not overtighten. Over tightening will cause the sight glass fitting to crack.**

Specifications

Type:

Cast sight glass

Material:

Body: brass* alloy

Windows: polycarbonate

Finish:

Rough brass*

Sizes:

1" M x F

Full flow

1/2" orifice (F x F)

17/32" orifice

1 1/4" M x F

1 1/2" F x F

2" F x F

All Full flow

*Contains lead. Not for use in water systems intended for human consumption.



Fire Protection Products, Inc

6241 Yarrow Dr., Suite A, Carlsbad, CA 92011-1541

For questions: 1 800 344-1822 • 1 800 344-3775 fax • www.fppi.com