



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 4/7/09

DAP[®] CAULK-BE-GONE[®] Latex Caulk Remover

- Softens caulk for easy removal
- Fast-acting formula
- Fresh scent
- Removes most types of caulks & sealants

Packaging: 5.5 fluid ounces (162 mL)
Color: Green Gel
UPC Number: 70798 18026, 70798 18045, 70798 11545

Company Identification:

Manufacturer: DAP Products Inc., 2400 Boston St., Ste. 200, Baltimore, Maryland 21224
Usage Information: DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST.
Order Information: 800-327-3339
Fax Number: 410-534-2650
Also, visit the DAP website at www.dap.com.

Product Description:

DAP[®] CAULK-BE-GONE[®] Latex Caulk Remover is specially formulated to soften most types of caulks and sealants for quick and easy removal from many surfaces. The fast-acting formula works in as little as two hours. CAULK-BE-GONE[®] is a green gel that stays where applied and is easy to differentiate from the caulking material. The fresh scent is non-offensive when used either indoors or out.

Suggested Uses:

To remove most types of caulks and sealants from most household surfaces.

1. Remove cap and cut nozzle to desired bead size.
2. Apply a same size bead of CAULK-BE-GONE[®] over the old caulk.
3. Allow the product to set until old caulk becomes soft (at least 2 hours). For previously applied silicone sealants, use DAP[®] Silicone-Be-Gone[™].
4. Remove old caulk using a putty knife or caulk removal tool.
5. Remove any remaining film with a razor blade or soft plastic abrasive pad.
6. Clean area with soap and water and allow to dry thoroughly before re-caulking.

For Best Results:

- To avoid substrate damage, always test for compatibility in an inconspicuous area prior to use.
- Mask the area adjacent to old caulk being removed.
- Product is safe for use on most surfaces. Do not use on soft plastics, vinyl, refinished porcelain, ABS plastic tubs and shower enclosures. Some fiberglass, other plastics or refinished surfaces may be affected.
- Immediately wipe off of painted/coated surfaces or wallpaper.
- Thicker bead, painted or acrylic caulks may take longer to soften or require multiple applications.
-

- Do not allow product to dry on surfaces (maximum 6 hours per application).
- Product cleans up with soap and water.

Physical & Chemical Characteristics:

Odor:	Fresh, clean scent
Consistency:	Smooth gel
Polymer:	None
Volatile:	97.0% ± 0.5% by weight
Flash Point:	None
Filler:	None
Specific Gravity:	1.03 ± 0.01
Solids:	3.5% ± 0.1% by Weight
Density:	8.64 ± 0.10 lbs./Gallon
Temperature Application Range:	30°F to 100°F
Freeze/Thaw Stability:	Passes 5 cycles
Shelf Life:	12 Months
Coverage:	30 ft. at 3/16" diameter bead or 2 bathtubs.
MSDS No.:	00077182001

Clean Up:

Product cleans up with soap and water.

Safety:

See product label and Material Safety Data Sheet for safety information. You can request an MSD sheet by visiting our website at www.dap.com or by calling 888-DAP-TIPS.

Warranty Information:

If not satisfied with product performance when used as directed, return used container and sales receipt to DAP Products Inc., Technical Customer Service, 2400 Boston St., Ste. 200, Baltimore, MD, 21224 for product replacement or sales price refund. DAP's liability is limited to product replacement or sales price refund.