



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 3/24/11

DAP® KWIK SEAL® Kitchen & Bath Adhesive Caulk-Clear

- **Waterproof seal**
- **Cured caulk is mold and mildew resistant**
- **Paintable**
- **Easy water clean-up**

Packaging: 5.5 fluid ounces (162 mL), 10.1 fl. oz. (300 mL)
Color: Clear
UPC Number: 70798 18008, 70798 18242

Company Identification:

Manufacturer: DAP Products Inc., 2400 Boston St., Ste. 200, Baltimore, Maryland 21224
Usage Information: Call 1-888-DAP-TIPS or visit dap.com & click on "Ask the Expert"
Order Information: 800-327-3339
Fax Number: 410-534-2650

Product Description:

DAP® KWIK SEAL® Kitchen & Bath Adhesive Caulk is an easy-to-use, multi-purpose adhesive caulk ideal for caulking and sealing in the bathroom and kitchen. It bonds like a glue and seals like a caulk. It is specially formulated to provide a watertight seal around tubs, sinks, showers and countertops. Cured caulk is mold and mildew resistant. It offers excellent adhesion, flexibility and durability. It tools easily and dries tack free in 15 minutes. Excellent for areas subject to water contact and high humidity. Dried surface cleans easily and is paintable with either latex or oil-based paint. Resists cracking, crumbling and shrinking. Resists abrasive chemicals. Easy water clean-up.

Suggested Uses:

Ideal for Caulking and Sealing:

- | | | |
|------------------------|--------------------------------|------------------------------------|
| • <i>Tubs</i> | • <i>Sinks</i> | • <i>Backsplashes</i> |
| • <i>Shower Stalls</i> | • <i>Countertops</i> | • <i>Toilets</i> |
| • <i>Fixtures</i> | • <i>Repairing Loose Tiles</i> | • <i>Other Cracks & Joints</i> |

Outstanding Adhesion to:

- | | | |
|-----------------------|-----------------------|---------------------|
| • <i>Ceramic Tile</i> | • <i>Plastic Tile</i> | • <i>Glass</i> |
| • <i>Porcelain</i> | • <i>Plaster</i> | • <i>Wood</i> |
| • <i>Metal</i> | • <i>Drywall</i> | • <i>Fiberglass</i> |

Surface Preparation & Application:

1. Surface must be clean, dry and free of all old caulk, dirt, dust and grease. Rubbing alcohol is recommended for removing soap film and soil.
2. Remove cap (from tube). Cut nozzle at a 45° angle to desired bead size.
3. Load into caulking gun (if using the 10.1 oz. cartridge).
4. Fill gap with caulk, pushing caulk ahead of nozzle.

5. If necessary, smooth bead of with finishing tool.
6. Clean up excess uncured caulk with a damp sponge before it skins over. Cured caulk must be cut or scraped away.
7. **Allow caulk to dry clear before painting with latex or oil-based paints.**
8. Reseal cartridge or squeeze tube for storage and reuse.

For Best Results:

- *Apply in temperatures above 40°F.*
- *Not for continuous underwater use. Do not apply product under shower door track or in closed applications.*
- *Joint gap should not exceed 3/8". If joint depth exceeds 3/8", use backer rod material.*
- ***Caulk applies white and dries clear in 7-14 days (longer in cool or humid conditions).***
- *Allow to dry and fully cure for at least 36 hours before exposing to water and moisture.*
- *Store caulk away from extreme heat or cold.*

Physical & Chemical Characteristics:

Vehicle:	Latex Polymer
Tooling Time:	10 Minutes
Tack-Free Time:	15 Minutes
Paintable:	Yes
Service Temperature Range (cured caulk):	-20°F to 180°F
Application Temperature Range:	40°F to 100°F
Coverage:	5.5 fluid ounces: 30 linear ft. at a 3/16" diameter bead or 2 bathtubs 10.1 fl. oz. = 55 linear ft. at a 3/16" diameter bead or 4 bathtubs
Odor:	Very Mild
Consistency:	Smooth and Creamy
Volatile:	Water
Filler:	Calcium Carbonate
Flash Point:	None
Solids:	57 ± 1% by weight
Weight per Gallon:	8.5 lbs. ± 0.05
Freeze Thaw Stability:	Passes 5 Cycles 0°F
Shelf Life:	12 months
MSDS No:	00077120001

Clean Up:

Clean up excess uncured caulk with a damp sponge before it skins over. Wash hands with warm water and soap. Excess dried caulk must be cut or scraped away.

Safety:

See product label and Material Safety Data Sheet (MSDS) for safety information. You can request an MSDS by visiting our website at dap.com or by calling 1-888-DAP-TIPS.

Satisfaction Guaranteed:

If product fails to perform when used as directed, return used container and sales receipt to DAP Products Inc., Technical Customer Service, 2400 Boston St., Ste. 200, Baltimore, MD 21224 for replacement product or sales price refund. DAP is not liable for incidental or consequential damages.