


Relays/Contactors/Transformers

Contactors

Honeywell offers definite-purpose contactors for heating, cooling and refrigeration applications.

- Replace most competitive models
- Compact size for easier installation
- Meet ARI 780 and UL/CSA/CUR standards.
- **New** Box lugs for easier installation (Deluxe PowerPRO)
- **New** Sealed coils extends life (Deluxe PowerPRO)
- **New** Baked finish for added durability



ECONOMY CONTACTORS								Cross Reference Information					
Poles	Contact Ratings (AFL @ 240, 277, 480, 600 Vac)	Input Voltage/Coil Voltage	Product Number	Dimensions (in.) H x W x D	Main Connections	Coil Connections	Contact Ratings (Resistive @ 240, 277, 480, 600 Vac)	Honeywell	Cutler Hammer	Furnas	Mars		
1 with shunt	30	24 Vac	DP1030A1001	2 7/32 x 2 1/2 x 3 5/16	Screw Terminal	Q	48 A	DP1030A1000	C25CNB130T	45EG10AJA	91320, 17311		
2	30	24 Vac	DP2030A1004	3 1/4 x 3 5/8 x 3 7/8			48 A	DP2030A1003	C25BNB230T	45EG20AJ	61354, 17321		
		120 Vac	DP2030B1003	2 7/32 x 3 5/16 x 2 5/32			40 A	DP2030B1002	C25BNB230A	45EG20AF	61346, 17322		
		208/240 Vac	DP2030C1002	2 7/32 x 2 1/2 x 3 5/16			40 A	DP2030C1001	C25BNB230B	45EG20AG	61347, 17323		
		24 Vac	DP2040A1003	2 3/8 x 3 5/16 x 2			50 A	DP2040A1002	C25BNB240T	45GG20AJ	61355, 17421		
120 Vac	DP2040B1002	50 A	DP2040B1001				C25BNB240A	45GG20AF	61356, 17422				
208/240 Vac	DP2040C1001	50 A	DP2040C1000				C25BNB240B	45GG20AG	61357, 17423				
POWERPRO CONTACTORS — ARI 780/790 RATED													
1 with shunt	25	24 Vac	DP1025A5006	2 7/32 x 2 1/2 x 3 5/16			Box Lug	Q	30 A	DP1025A5005	C25DND230B	45DG10AJA	61315
2	30		DP1030A5014	2 7/32 x 2 1/2 x 3 5/16					48 A	DP1030A5013	C25ENF440A	45EG10AJA	13101, 61320, 61720
	40		DP1040A5005	2 23/64 x 2 1/2 x 3 5/16	50 A	DP1040A5004			C25ENF440B	45GG10AJA	61330		
	30	24 Vac	DP2020A5022	2 7/32 x 2 1/2 x 3 5/16	30 A	DP2020A5021			C25ENF440T	45CG20AJ	61310		
		120 Vac	DP2020B5039	2 7/32 x 2 1/2 x 3 5/16	30 A	DP2020B5038			C25DND230A	45CG20AF	61336, 14122		
24 Vac		DP2030A5005	3 1/4 x 2 5/8 x 3 3/4	48 A	DP2030A5004	C25DND230T			45EG20AJ	61345, 13104, 91321, 60510			
24 Vac		DP2030A5013	3 1/4 x 2 5/8 x 3 3/4		DP2030A5012					60510			
120 Vac	DP2030B5004	2 7/32 x 3 5/16 x 2 5/32	DP2030B5003		C25DND230A	45EG20AF			61346, 13105,				
120 Vac	DP2030B5012	2 5/16 x 3 5/16 x 2 5/32	DP2030B5011		Not Available				60031				
208/240 Vac	DP2030C5003	2 7/32 x 2 1/2 x 3 5/16	DP2030C5002		C25DND230B	45EG20AG			61347, 13106, 60512, 60032				
208/240 Vac	DP2030C5011		DP2030C5010		Not Available	Not Available	60512, 91323						
40	24 Vac	DP2040A5004	2 23/64 x 3 3/16 x 1 15/16	DP2030D5002	Not Available	Not Available	60,153						
	120 Vac	DP2040B5003		DP2040A5003	C25DNF240T	45GG20AJ	13107 91421, 61355, 61755, 60525,						
	208/240 Vac	DP2040C5002		DP2040B5002	C25DNF240A	45GG20AF	13108, 91422, 61356, 61756,						
	208/240 Vac	DP2040C5002		DP2040C5001	C25DNF240B	45GG20AG	13109, 91423, 61357, 61757, 60527, 14423						
3	30	24 Vac	DP3030A5004	3 7/64 x 3 5/8 x 2 13/32	Q, S	40 A	DP3030A5003	C25DND330T	42BF35AJ	61430, 13113, 60515, 13007, 91331			
		120 Vac	DP3030B5003				DP3030B5002	C25DND330A	42BF35AF	61431, 13114, 91332			
		208/240 Vac	DP3030C5002				DP3030C5001	C25DND330B	42BF35AG	61432, 13115, 91333, 60517, 13009			
	40	24 Vac	DP3040A5003			50 A	DP3040A5002	C25DNF340T	42CF35AJ	60530, 14423, 61445, 13013 91431			
		120 Vac	DP3040B5002				DP3040B5001	C25DNF340A	42CF35AF	61446			
		208/240 Vac	DP3040C5001				DP3040C5000	C25DNF340B	42CF35AG	60532, 60182, 61447, 13015, 91433			
	50	24 Vac	DP3050B5002			63 A	DP3050A5001	C25DNJ350T	42DF35AJ	61460, 13619, 91531			
		120 Vac	DP3050B5001				DP3050B5000	C25DNJ350A	42DF35AF	61461			
		208/240 Vac	DP3050C5010				DP3050C5009	C25DNJ350B	42DF35AG	60217, 60202, 61462, 13621, 91533			
	60	24 Vac	DP3060A5001			75 A	DP3060A5000	C25FNF360T	42EF35AJ	61470 13625 91631			
		120 Vac	DP3060B5010				DP3060B5009	C25FNF360A	42EF35AF	61471			
		208/240 Vac	DP3060C5009				DP3060C5008	C25FNF360B	42EF35AG	60227, 60207, 61472, 13627, 91633			
75	24 Vac	DP3075A5017	95 A	DP3075A5016	C25FNF375T	42FE35AJ	60235, 61475, 13240, 91731						
	120 Vac	DP3075B5016		DP3075B5015	C25FNF375A	42FE35AF	60237, 61476						
	208/240 Vac	DP3075C5015		DP3075C5014	C25FNF375B	42FE35AG	60245, 61477, 13242, 91733						
90	120 Vac	DP3090B5007	120 A	DP3090B5006	C25GNF390A	42GE35AF	61491						
	208/240 Vac	DP3090C5006		DP3090C5005	C25GNF390B	42GE35AG	60247, 61492, 13262						
	24 Vac	DP4040A5002		50 A	DP4040A5001	C25ENF440T	42CF25AJ	61450, 13016					
120 Vac	DP4040B5001	DP4040B5000	C25ENF440A		42CF25AF	61451							
208/240 Vac	DP4040C5010	DP4040C5009	C25ENF440B		42CF25AG	61452							

Connectors:	BHS — Binding Head Screw; Q — Quick Connect; SS — Sems Screw; CHS — #10-32 Combination Head Screw; S — #6 Screw; TCS — Terminal Clamp Screw; LC — Lug Connector	Approvals:	UL, CSA
Temp Rating:	-4° F to 149° F	ARI - 780:	500,000 cycle mechanical life; 200,000 cycle electrical life; 10,000 cycle recycle life