

## LIQUID-TIGHT CONDUIT FITTINGS



### Liquid-Tight Conduit Fittings – 90 Degrees

PART NO	DESCRIPTION	CASE QTY	CASE REQ
PD455006	Liquid-Tight Conduit Fitting - 1/2 in. 90 Degree	10	Yes
PD455008	Liquid-Tight Conduit Fitting - 3/4 in. 90 Degree	100	Yes

### Liquid-Tight Conduit Fittings – 90 Degrees (Quick Twist)

PART NO	DESCRIPTION	CASE QTY	CASE REQ
455002	Liquid-Tight Conduit Fitting - 1/2 in. 90 Degree (Quick Twist)	10	Yes
455004	Liquid-Tight Conduit Fitting - 3/4 in. 90 Degree (Quick Twist)	10	Yes

## FUSES & FUSE HOLDERS



### Fuses – Branch Circuit (RK5 Cartridge Type)

- RK5 Dual-Element Time Delay branch circuit fuses
- Maximum interrupting rating: 200,000A RMS Symmetrical

PART NO	FUSE MOUNTING (CARTRIDGE)	CURRENT RATING (A)	MAX VOLT RATING (VAC)	OVERALL LENGTH (IN)	DIAMETER (IN)	EDISON CROSS REFERENCE	BUSSMAN CROSS REFERENCE	GOULD CROSS REFERENCE	LITTELFUSE CROSS REFERENCE	DIVERSITECH CROSS REFERENCE
44-ECNR-15-10PK	Ferrule	15	250	2	9/16	ECNR15	FRN-R-15	TR15	FLNR15	7-CRNR15
44-ECNR-20-10PK	Ferrule	20	250	2	9/16	ECNR20	FRN-R-20	TR20	FLNR20	7-CRNR20
44-ECNR-25-10PK	Ferrule	25	250	2	9/16	ECNR25	FRN-R-25	TR25	FLNR25	7-CRNR25
44-ECNR-30-10PK	Ferrule	30	250	2	9/16	ECNR30	FRN-R-30	TR30	FLNR30	7-CRNR30
44-ECNR-35-10PK	Ferrule	35	250	3	13/16	ECNR35	FRN-R-35	TR35	FLNR35	7-CRNR35
44-ECNR-40-10PK	Ferrule	40	250	3	13/16	ECNR40	FRN-R-40	TR40	FLNR40	7-CRNR40
44-ECNR-45-10PK	Ferrule	45	250	3	13/16	ECNR45	FRN-R-45	TR45	FLNR45	7-CRNR45
44-ECNR-50-10PK	Ferrule	50	250	3	13/16	ECNR50	FRN-R-50	TR50	FLNR50	7-CRNR50
44-ECNR-60-10PK	Ferrule	60	250	3	13/16	ECNR60	FRNR-R-60	TR60	FLNR60	7-CRNR60
44-ECNR-100-5PK	Knife w/Rejection	100	250	5-7/8	1-1/16	ECNR100	FRN-R-100	TR100	FLNR100	—
44-ECSR-20-10PK	Ferrule	20	600	5	13/16	ECSR20	FRS-R-20	TRS20	FLSR20	—
44-ECSR-30-10PK	Ferrule	30	600	5	13/16	ECSR30	FRS-R-30	TRS30	FLSR30	—
44-ECSR-60-10PK	Ferrule	60	600	5-1/2	1-1/16	ECSR60	FRS-R-60	TRS60	FLSR60	—
44-ECSR-100-5PK	Knife w/Rejection	100	600	7-7/8	1-7/64	ECSR100	FRS-R-100	TRS100	FLSR100	—
44-ECSR-125-1PK	Knife w/Rejection	125	600	9-5/8	1-19/32	ECSR125	FRS-R-125	TRS125	FLSR125	—

### FUSES – CONTROL CIRCUIT

All control circuit fuses are sold in packs of five.



#### Fuses – Control Circuit (Glass – Fast Acting 15 mm/0.591 in.)

PART NO	CURRENT RATING (A)	MAX VOLT RATING (VAC)	OVERALL LENGTH (IN)	DIAMETER (IN)	BUSSMAN CROSS REF	GOULD CROSS REF	LITTELFUSE CROSS REF
46-22863-82-5PK	2	350	0.591 (15 mm)	0.177 (4.5 mm)	—	—	2AG-229-002



#### Fuses – Control Circuit (Glass – Fast Acting 20 mm/0.788 in.)

PART NO	CURRENT RATING (A)	MAX VOLT RATING (VAC)	OVERALL LENGTH (IN)	DIAMETER (IN)	BUSSMAN CROSS REF	GOULD CROSS REF	LITTELFUSE CROSS REF
44-GMA1A-5PK	1	250	0.788 (20 mm)	0.197 (5 mm)	GMA1A	GGM1A	235-1
44-GMA2A-5PK	2	250	0.788 (20 mm)	0.197 (5 mm)	GMA2A	GGM2A	235-2
44-GMA3A-5PK	3	250	0.788 (20 mm)	0.197 (5 mm)	GMA3A	GGM3A	235-3
44-GMA5A-5PK	5	125	0.788 (20 mm)	0.197 (5 mm)	GMA5A	GGM5A	235-5