

# Air Releases & Controls



HAE1

### HARVARD®

#### All Plastic Deep Well Air Release Features:


- Maintains proper ratio of air to water in submersible water systems.
- All polyethylene construction eliminates corrosion.
- Includes gauge port and 0-40 psi limited bleed adjustment.
- **NO LEAD - Third party certified to NSF/ANSI 372.**
- **Made in USA.**



BAR125N

#### Brady Plastic Deep Well Air Release Features:


- Maintains the proper ratio of air to water.
- Constructed of ABS resin grade plastic.
- Non-corrosive, non-conductive and completely serviceable.
- Release mechanism consists of a Buna-N procession ball & 316 stainless steel spring.
- Factory set at 20 P.S.I., adjustable from 0 to 40 P.S.I.



WJ1NL

#### Deep Well Air Release Features:

- Maintains proper ratio of air to water in submersible water systems.
- Deluxe deep well air release features ABS float and molded or cast body which prevents galvanic action at pump tank tapping.
- **WJ1NL NO LEAD**
- WJ1NL Imported.




HF93B1



SWCL

#### Shallow Well Control Features:

- Preserves correct proportion of water and air in shallow well reciprocating pump systems.
- **SWCLNL NO LEAD**
- Imported.



Part Number	Tapping	Manufacturer	Ctn Qty
<b>All Plastic Deep Well Air Release</b>			
HAE1	1 1/4"	Harvard	49
BAR125N	1 1/4"	Brady	50
<b>Deep Well Air Release</b>			
WJ1NL	1 1/4"	Ametek	20
HF93B-1	1 1/4"	Johnson	50
<b>Shallow Well Control</b>			
SWCLNL	1 1/4"	NO LEAD Ametek	20