

ĹOW LEAD

# **PFXAF Premium Series** Frost Proof Yard Hydrants

## Product Features

- Lever control with variable flow
- Heavy-duty solid no lead brass hose adapter
- Pipe and rod are galvanized to prevent rust
- Head and lever can be padlocked when not in use to prevent unauthorized use
- . Drains below the frost line once hydrant is shut off
- Inlet: 3/4" NPT in no lead brass casting
- Outlet: 3/4" no lead brass hose thread
- Stainless steel operating rod thru teflon packing
- · Automatic self-adjusting plunger
- 1" galvanized pipe and 7/16" galvanized operating rod
- Overall length is 34" plus bury depth (bury depth is stenciled on pipe)

### Parts Available


#### **PFXAFHDL** - Lever control (A)

#### PFAF7500RK

Repair Kit for PFAF7500 Series Yard Hydrant includes one each of the following: - Valve stem packing

- Draw straps (pair)
- Pivot connector and nuts - Plunger assembly
- Packing nut

		OVERALL LENGTH
	DESCRIPTION	(INCHES)
PFXAF7501	1 FT BURY PREMIUM FREEZELESS YARD HYDRANT	45.5
PFXAF7502	2 FT BURY PREMIUM FREEZELESS YARD HYDRANT	57.5
PFXAF7503	3 FT BURY PREMIUM FREEZELESS YARD HYDRANT	69.5
PFXAF7504	4 FT BURY PREMIUM FREEZELESS YARD HYDRANT	81.5
PFXAF7505	5 FT BURY PREMIUM FREEZELESS YARD HYDRANT	93.5
PFXAF7506	6 FT BURY PREMIUM FREEZELESS YARD HYDRANT	105.5
PFXAF7507	7 FT BURY PREMIUM FREEZELESS YARD HYDRANT	117.5





Made in U.S.A.

- A Lever Control
- B Draw Straps
- C SS Operating Rod
- D Heavy-Duty Solid
- No Lead Brass Hose Adapter E - Extra Thick Walled
- Head Casting
- F Pivot Connector withTwo Nuts
- G USA Schedule 40 Galvanized Pipe
- H Extra Thick Walled No Lead Valve Body
- I Patented Plunger Arrangement
- Krayton G Cup Seals
- J Beveled Bibb Washer
- K SS Spring
- L Plunger on Swivel

## Warranty and Codes

This PROFLO product carries a 1-year limited warranty.

Ground Level



PFXAF SERIES Low-Lead Compliant

Hydrant stands about

34" above ground

Hydrant bury depth or depth water lines are buried

underground.

(C