

LN-715

Interior

A durable construction adhesive that provided an exceptional waterproof bond under extreme conditions.



PRODUCT DESCRIPTION

LIQUID NAILS® Tub Surround & Shower Wall Adhesive is a high-solids, VOC compliant adhesive for tub and shower surrounds designed to provide a water resistant bond between all types of tub and shower surround materials, including polystyrene, and all types of wall materials, including existing tile. This product can be used as a caulk to seal joints between tubs and surrounds and between surround panels. LIQUID NAILS Tub Surround & Shower Wall Adhesive is resistant to mold and mildew. This unique formulation meets the requirements of all air quality regulations and will not soften or distort tub and shower surround materials. LIQUID NAILS Tub Surround & Shower Wall Adhesive meets the requirements of the US Green Building Council LEED and the National Association of Home Builders Residential Green Building programs.

RECOMMENDED FOR bonding most plastic and fiberglass tub & shower surrounds to:

- Drywall
- Plywood
- Greenboard
- Cement backerboard
- Ceramic tile

NOT RECOMMENDED FOR uses other than tub & shower surrounds. Not recommended for water immersion conditions.

Please research all installation instructions and read entire label for safety, health & environmental information prior to use.

Look for other LIQUID NAILS products which are right for your specific project.

PRODUCT ADVANTAGES

- No burn through
- Heat and steam resistant
- Great for plastic, fiberglass and polystyrene tub & shower units
- Light color won't show through
- Water resistant
- VOC Compliant
- Interior
- 100% Satisfaction Guaranteed



SURFACE PREPARATION

Make sure that all surfaces are clean, dry, structurally sound and free of any loose paint or other materials. Sand and roughen high gloss paint.

APPLYING THE PRODUCT

For applications over ceramic tile, sand surface before applying adhesive. Apply adhesive to surround panel in a ¼ inch wide continuous bead approximately one inch from the edges of the panel. An "S" or "X" shaped bead may be applied to the center portion of the panel. Press the panel into place on the wall within 15 minutes of the adhesive application. Press firmly into place. Repeat for remaining panels and corner units. To develop more tack, peel panels back from wall for 3 minutes, then press back into place. Bracing may be needed if panels do not lie flat. For overlap areas and edges, this adhesive may be used as a caulk. Panel edges and seams may be caulked after 24 hours. Allow adhesive and caulk to dry overnight prior to use.

Application Rate: 32 linear feet per tube. A typical surround will require approximately 3 tubes of adhesive for installation, including caulking.

It is important for proper installation that each panel be vented according to the following directions. Venting method: Apply LN-715 adhesive and press panel firmly to wall, then pull away. Wait 3-5 minutes, then press panel firmly back into place. For proper adhesion, after 20-30 minutes go around entire tub surround and press firmly over all flat surfaces. If any edges lift up, tape them to the wall with masking tape until adhesive dries. Let cure 24 hours.

CLEAN-UP

Use water for wet adhesive. Scrape off dried adhesive. Residue may be removed by applying mineral spirits to a cloth and wiping.

DISPOSAL

Place empty containers in normal refuse for disposal. Remove residual product from the container, allow product to dry, and dispose of in conjunction with normal household waste. Contact your sanitation department or household hazardous waste coordinator for information concerning possible re-use of unused caulks and sealants.

EAD-C8

LIMITED WARRANTY

Macco warrants satisfaction with this product when handled and applied according to label instructions. If this product is not as warranted, please call 1-800-634-0015 for refund or product replacement details. This warranty excludes labor or the cost of labor and is given as the exclusive warranty and remedy. **No warranty of merchantability, fitness for purpose or other warranty, express or implied, is made.** Macco shall not be liable for any special, incidental or consequential damages. Some states do not allow the exclusion of incidental or consequential damages, so the limitations may not apply. This warranty gives specific legal rights. You may also have other rights that vary from state to state.

WARNING! CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. MAY BE HARMFUL IF SWALLOWED. USE ONLY WITH ADEQUATE VENTILATION. KEEP OUT OF THE REACH OF CHILDREN.

This product contains a chemical known to the state of California to cause cancer and birth defects, or other reproductive harm. Contains Crystalline Silica. If sanding, wear a dust mask to avoid breathing of sanding dust. Avoid contact with eyes and skin. **FIRST AID:** For skin contact, wash thoroughly with soap and water. If any product remains, gently rub with petroleum jelly, vegetable or mineral/baby oil then wash again with soap and water. Repeat as needed. Remove contaminated clothing. For eye contact, flush immediately with plenty of water for at least 15 minutes. **Get medical attention.** If swallowed, **get medical attention immediately.** If inhalation causes discomfort, remove to fresh air. If discomfort persists or breathing difficulty occurs, get medical attention. **For emergency information, customer service, MSDS or additional safety and chronic hazard information, call 1-800-634-0015. KEEP FROM FREEZING.**

MAC133-1006

LN-715

TECHNICAL INFORMATION

Base: Vinyl Acrylic

Type: Water borne

Color: Bright white

Appearance: Smooth Paste

Application Temperature:
40° to 100° F (4° to 38° C)

Service Temperature:
-20 to 200° F (-29° to 93° C)

Adhesion: Good to most common building substrates

Shear Strength:
24 hours – 300 psi
7 days – 380 psi

Consistency: Smooth paste

Durability: Excellent

Flexibility: Good to -10° F (-23° C)

Volume Shrinkage: 40%

Slump: Max 0.15"

Shore "A" Hardness: 60

Water Resistance: Good

Freeze-Thaw Stable: Passes 5 cycles

Bleed: None

Staining: None

Odor: Mild Acrylic

Aging: Will not become brittle

Tack Free Time: Tack at drying time – none

Tack at 24 hours – none

Drying Time: Sets in 24 hours. Allow 5 days to completely dry

Weight Per Gallon: 12.5 pounds (5.54 kg)

Viscosity: 350,000 to 400,000 CPS

Solids: 75%

Flammability: Nonflammable

Flash Point: Greater than 200°F (93°C)

Coverage: 30 lineal ft. (9.14 lineal meters) using 1/4" (.64cm) bead

Shelf Life: 12 months from date of purchase

MAX VOC: 28 g/L

Akzo Nobel Paints LLC
15885 West Sprague Rd.
Strongsville, OH 44136

www.liquidnails.com

Customer Service 1-800-634-0015