

# WIRE MANAGEMENT

## Direct Burial/Submersible Splice Kits with Heat Shrink

### Easy-Splice™

#### SK Series



#### SPECIFICATIONS

- UL Listed.
- Temperature Rating: 105 °C. 600V Max.

#### FEATURES

##### Copper Butt Splice Kits (SKCB)

- Mechanical copper butt splice and a heavy wall heat shrink tubing to create a fully insulated splice for copper conductors only.

##### UF Cable Splice Kit (SKAB)

- For simplified splicing of UF cable designed with heavy wall heat shrink with sealant.
- This kit will accommodate 14/3 through 8/3 with ground UF cable and create a direct burial splice. Contains one four-position connector.

##### Dual Rated Butt Splice Kits (SKDB)

- Mechanical dual rated splice and matched heavy wall heat shrink tubing to create an insulated splice for copper and/or aluminum cables.

##### UF Stretcher Kit (SKUF)

- Eliminates the need for using two connectors and a short piece of cable when repairing damaged UF cable.
- Includes one 11.5" connector that will accommodate 14/3 without GRD minimum and 8/3 with GRD maximum. 600 Volt, 105°C.
- Utilizes heavy wall shrink with sealant for a quick and reliable repair.

CAT. NO.	RANGE	STD. CTN. QTY.
SKCB-8	#14 to #8 AWG	24
SKCB-2	#8 to #2 AWG	24
SKAB-2	#8 to #2 AWG	24
SKAB-0	#6 to 1/0 AWG	24
SKAB-250	1/0 AWG to 250 MCM	12
SKDB	14/3 to 8/3	24
SKUF	14/3 to 8/3	12