



## SPECIAL INSTRUCTIONS

The Brass Packing Nut located on the head of the Simmons Frost-Proof Yard Hydrant has been factory adjusted. If leakage should occur upon installation or after usage, you may find it necessary to slightly tighten the Brass Packing Nut.

**CAUTION: Do not over-tighten Brass Packing Nut. Damage will occur to inner O rings. Do not leave hose attached in freezing temperature as it may prevent proper drainage of the riser pipe via shut-off valve drain hole.**

## Yard Hydrants - LENGTHS

Bury Depth	Pipe Length	800 Series		4800, 5800 & 900 Series			Overall Length
		Model	Overall Length	Model	Model	Model	
1 ft.	30"	800	40"	4800	5800	900	39 1/4"
1 1/2 ft.	38"	801	48"	4801	5801	-	47 1/4"
2 ft.	44"	802	54"	4802	5802	902	53 1/4"
3 ft.	56"	803	66"	4803	5803	903	65 1/4"
4 ft.	68 1/2"	804	78 1/2"	4804	5804	904	77 3/4"
5 ft.	80 1/2"	805	90 1/2"	4805	5805	905	89 3/4"
6 ft.	92 1/4"	806	102 1/4"	4806	5806	906	101 1/2"
7 ft.	104"	807	114"	4807	--	--	113 1/4"
8 ft.	116"	808	126"	4808	--	--	125 1/4"

If hydrant will not shut off completely, the plunger in the bottom of the hydrant can be lowered by raising the point of contact of the square head set screw on the brass rod.

To prevent unauthorized use, handle on 800, 900, 4800 and 6800 Series can be padlocked by inserting padlock into holes provided in handle and head.

The Frost Proof Yard Hydrant provides running water for lawn and garden, livestock and fire protection all year even in sub-zero temperatures. The shut-off valve operates below the frost line. Hydrant cannot freeze because when it is closed, all water in the standpipe drains out a hole in the valve which is set in the

ground below the frost line. Hydrant spout operates at a convenient height (24 inches) from the ground level so that it can spill into a stock tank. Adapter (No. 8828) is threaded for 3/4" hose. Hydrant can be easily installed anywhere water is supplied under pressure.