

## ***NES Series Water Softeners***

***Easy to Use And Budget Friendly!***



**Easy To Program.** Just push the button to set the time of day and hardness.

**Safety Brine Valve.** Eliminates messy overflow should a malfunction occur.

**Optional Advanced Programming.** Adjustment of each cycle duration; regeneration time; and days over-ride.

**Salt Shelf.** Allows the use of inexpensive salt and reduces the chance of salt bridging and mushing.

**Rugged Resin Tank.** Fiberglass construction, will never rust or corrode.

**Vortex Distributor.** Scrubs the resin each regeneration to extend the life of the softener.

**Self Leveling Base.** Compensates for unlevel floor.

**Rugged Valve.** Motorized piston for years of trouble free service.

**Quick Release Drain Fitting.** No threads to Leak. Merely pull clip to remove drain fitting.

**Push-In Brine Line Fitting.** Eliminates confusing ferrules and nuts that can cause leaks.

**Stainless Steel Bypass.** Operate with single handle. 3/4" or 1" female threads.



# NES SERIES

## SPECIFICATIONS

Model Number	Grain Capacity		Flow Rate (gpm)		Salt Storage (lbs.)	Dimensions *Inlet Height				Pipe Size
	Max.	Min.	Peak	Service		A	*B	C	D	
NES-1-S	30,000	24,000	14	8	200	56"	49.75"	27"	15"	3/4" or 1"
NES-1-5-S	45,000	36,000	13	10	200	62"	56"	28"	15"	
NES-2-S	60,000	48,000	14	12	200	56"	49.75"	30"	15"	
NES-2-5-S	75,000	60,000	15	14	200	62"	56"	32"	18"	

NOTE: If a 1" bypass is desired change suffix to 1S, example NES-1-1S.

## SPACE-MAKER

Model Number	Grain Capacity		Flow Rate (gpm)		Salt Storage (lbs.)	Dimensions *Inlet Height				Pipe Size
	Max.	Min.	Peak	Service		A	*B	C	D	
NECS-1-S	30,000	24,000	14	8	150	43"	36.50"	23"	13"	3/4" or 1"

NOTE: If a 1" bypass is desired change suffix to 1S, example NECS-1-1S.

NOTE: Service flow rate of control valve (only) is 20gpm @ 15 psig drop.

**NECS**



**NES**

