8840200

Trim for ½" & ¾" Volume control

STANDARDS

- Compliant with ASME A112.18.1-B125.1 requirements
- Certified By CSA international

Finishes	8840200PC	8840200BN	8840200TB
Polished Chrome	Χ		
Brushed Nickel		Χ	
Tuscan Bronze			Χ

Features	8840200PC	8840200BN	8840200TB
Solid Brass Construction	X	Χ	Χ
Ceramic Disc Valving	X	Χ	Χ
3/4" NPT or 1/2" NPT inlet	X	Χ	Х
Progressive Volume Control	X	Χ	Х
Kit Includes Trim	X	Χ	Х
Step-By-Step Installation Instructions	X	Χ	Х
Limited Lifetime Warranty	X	Χ	Χ

Project: _____Contractor: _____



8875000

Showerhead Kit

STANDARDS

- Compliant with ASME A112.18.1-B125.1 requirements Certified By CSA international

Finishes	8875000PC	8875000BN	8875000TB
Polished Chrome	Χ		
Brushed Nickel		Χ	
Tuscan Bronze			Χ

Features	8875000PC	8875000BN	8875000TB
Showerhead Kit with Matching 6" arm and flange	Χ	Χ	Χ
Delivers 2.5gpm at 80psi MAX	Χ	Χ	Χ
Showerhead features Rotating Ball Joint	Χ	Χ	Χ
1/2" NPT Inlets	Χ	Χ	Χ
Self Cleaning Spray Nozzles	Χ	Χ	Χ
Step-By-Step Installation Instructions	Χ	Χ	Χ
Limited Lifetime Warranty	Χ	Χ	Х



Project:	 	 	
Contractor:			



8872100

Body Spray


STANDARDS

- Compliant with ASME A112.18.1-B125.1 requirements
- Certified By CSA international

Finishes	8872100PC	8872100BN	8872100TB
Polished Chrome	Χ		
Brushed Nickel		Χ	
Tuscan Bronze			Χ

Features	8872100PC	8872100BN	8872100TB
Invigorating Body Jet	X	Х	Χ
Delivers 2.5gpm at 80psi MAX	X	Χ	Х
Sprayer features 30° Rotation	X	Χ	Х
1/2" NPT Inlets	X	Χ	Х
Self Cleaning Spray Nozzles	X	Х	X
Step-By-Step Installation Instructions	X	X	Χ
Limited Lifetime Warranty	Х	Χ	Х

Project: ₋				
Contract	or:			





8871100


Thermostatic Trim Kit for 3/4" Valve

STANDARDS

- Compliant with ASME A112.18.1-B125.1
- Compliant with ASSE 1016
- Certified by CSA International

Finishes	8871100PC	8871100BN	8871100TB
Polished Chrome	Χ		
Brushed Nickel		Χ	
Tuscan Bronze			Χ

Features	8871100PC	8871100BN	8871100TB
Solid Brass Construction	Х	Х	Χ
3/4" Thermostatic Valve featuring Ceramic Discs	Χ	Χ	Χ
Kit Includes Trim & Thermostatic cartridge	Χ	Χ	Χ
High Flow Thermostatic Valve Supports Multiple Outlets	Χ	Χ	Χ
3/4" NPT Inlets	Χ	Χ	Χ
Safety High Limit Temperature Stop	Χ	Χ	Χ
Step-By-Step Installation Instructions	Χ	Χ	Χ
Limited Lifetime Warranty	Χ	Χ	Х



Project:			
Contractor:			

