

**MADERA YOUTH™ FloWise® 14" HEIGHT
ELONGATED FLUSHOMETER TOILET**

- Floor mount flushometer valve toilet
- Vitreous china
- High Efficiency, Low Consumption. Operates in the range of 1.28 gpf to 1.6 gpf (4.8 Lpf to 6.0 Lpf)
- Meets definition of HET (High Efficiency Toilet) when used with a high efficiency flush valve (1.28 gpf)
- Fully glazed 2-1/8" trapway
- Elongated bowl
- 10" or 12" roughing-in
- 14" rim height
- Condensation channel
- Powerful direct-fed siphon jet action
- 10" x 12" water surface area
- 1-1/2" inlet spud
- 2 bolt caps
- 100% factory flush tested
- TAS Compliant

2599.001 Elongated bowl only, top spud

Component Parts:

- 047007-0070A** Inlet Spud (furnished with bowl)
- 481310-0200A** Bolt caps with retainers (furnished with bowl)

Nominal Dimensions:

718 x 356 x 356mm
(28-1/4" x 14" x 14")

Fixture only, less seat and flush valve

Recommended working pressure—between
25 psi at valve when flushing and 80 psi static

Compliance Certifications -

- Meets or Exceeds the Following Specifications:**
- ASME A112.19.2-2008 / CSA B45.1-08 for Vitreous China Fixtures



SEE REVERSE FOR ROUGHING-IN DIMENSIONS

To Be Specified:

- Color: White
- Seat: TAS compliant seat recommendation
 - For ages 5 through 8: American Standard #5901.100 Heavy duty open front less cover
 - For ages 9 through 12: American Standard #5905.100 Extra heavy duty open front less cover or #5910.100 Extra Heavy Duty Plus open front less cover
- Flushometer Valve:
 - 1.6 gpf:
 - Sensor-Operated: American Standard Selectronic® DC Power #6065.161.002 (Top Spud)
 - Manual: American Standard #6047.161.002 (Top Spud)
 - 1.28 gpf:
 - Sensor-Operated: American Standard Selectronic® DC Power #6065.121.002 (Top Spud)
 - Manual: American Standard #6047.121.002 (Top Spud)

