

## Specifications

### PFXCH SERIES

# Corrugated Water Heater Connector



#### Product Features

- Stainless steel corrugated
- Kink resistant
- IAPMO listed
- NSF/ANSI 61 compliant
- AB 1953 compliant
- ASME A112.18.6
- Max Pressure: 125 psi
- Working Temperature: 40°F–160°F
- Max Temperature: 180°F
- Built-in dielectric sleeve to prevent possible galvanic corrosion
- 100% Leak tested

#### Materials

- Tubing: Stainless steel 304 (ASTM A240)
- Nut: Chrome-plated brass 3771
- Gasket: High-quality EPDM

#### Warnings

Exposure to elevated levels of inorganic material (including but not limited to Na, Mg, Ca, and K) may lead to accelerated corrosion, especially in high temperature and high water velocity environments.

#### Product Specifications

Model Number	Description	Length (in.)	Length (mm)
PFXCHF18N	LF 3/4 FIPXPUSH 18 SS COR WHTR CONN	18"	457.2mm
PFXCHFT18N	LF 3/4 FIP 18 SS COR WHTR CONN	18"	457.2mm
PFXCHFT24N	LF 3/4 FIP 24 SS COR WHTR CONN	24"	609.6mm
PFXCHGT18	LF 1 FIP 18 SS COR WHTR CONN	18"	457.2mm
PFXCHGT24	LF 1 FIP 24 SS COR WHTR CONN	24"	609.6mm
PFXCHHT18	LF 1-1/4 FIP 18 SS COR WHTR CONN	18"	457.2mm
PFXCHJT18	LF 1-1/2 FIP 18 SS COR WHTR CONN	18"	457.2mm
PFXCHGFT24N	LF 1X3/4 FIP 24 SS COR WHTR CONN	24"	609.6mm
PFXCHHGT24	LF 1-1/4X1 FIP 24 SS COR WHTR CONN	24"	609.6mm
PFXCHFM18N	LF 3/4 MXF 18 SS COR WHTR CONN	18"	457.2mm
PFXCHFM24N	LF 3/4 MXF 24 SS COR WHTR CONN	24"	609.6mm
PFXCHF18NA	LF 3/4 FIPXSWT 18 SS COR WHTR CONN	18"	457.2mm
PFXCHF24NA	LF 3/4 FIPXSWT 24 SS COR WHTR CONN	24"	609.6mm
PFXCHF18P	LF 3/4 FIP X F1807 18 SS WHTR CONN	18"	457.2mm
PFXCHF24P	LF 3/4 FIP X F1807 24 SS WHTR CONN	24"	609.6mm
PFXCHF18PP	LF 3/4 FIP X F1960 18 SS WHTR CONN	18"	457.2mm
PFXCHF24PP	LF 3/4 FIP X F1960 24 SS WHTR CONN	24"	609.6mm

#### Warranty and Codes

These PROFLO products carry a 1-year limited warranty.



PFXCHF18N