

Tank Installation Packages - 1 1/4" Side Discharge

 ALL tank installation package components contain no lead and are third party certified to NSF/ANSI 372.



IP125BSNL	CIC125BSNL	NO LEAD Brass	4 1/4"	\$ 142.38
IP125BSNL 40/60	CIC125BSNL	NO LEAD Brass	4 1/4"	142.38
CIC125BSNL	1 1/4" Short Ca	st NO LEAD Brass C	ross.	NO LEAD
• 9013FSG2	30/50 or 40/60	Pressure Switch.		(Pb) < 0.25% Pb
• B80-1/4 x 3	Brass Nipple.			average
• EIPG1002-4LNL	100lb NO LEAD	Pressure Gauge		
IRV50NL	1/2" NO LEAD B	rass Relief Valve		
HNKD75NL	3/4" NO LEAD B	rass No Kink Boiler	Drain	



IP3125BSENL	CIC3125BSENL NO LEAD Brass 4 1/2"	\$ 117.95
CIC3125BSENL	1 1/4" Short Cast NO LEAD Brass Tank Cross	
• 9013FSG2	30/50 Pressure Switch.	NO LEAD
• B80-1/4 x 3	Brass Nipple.	(Pb) < 0.25% Pb
• EIPG1002-4LNL	100lb. NO LEAD Brass Pressure Gauge.	average
• IRV75NL	3/4" NO LEAD Brass Relief Valve.	
• HNKD75NL	3/4" NO LEAD Brass No Kink Boiler Drain	



IPS125SSNL	CICS125SS	Stainless Steel	4 1/2"	\$ 183.36
see above	1" Short Cast S	Stainless Steel Tank C		NO LEAD
• 9013FSG2 30/50	Pressure Switch	h.		(Pb) < 0.25% Pb
• SS80-1/4 x 3	Stainless Stee	l Nipple.		average
 EIPG1002-4LNL 	100lb NO LEAD	O Pressure Gauge		
• IRV75SS	3/4" Stainless	Steel Relief Valve		
 IHBB75SS 	3/4" Stainless	Steel Hose Bibb		
• HTST60-1/2SS	1/2" x 60" Sta	inless Steel PTFE Tape	е	



CWM125BSNL	No Lead brass	4 3/4"	\$ 132.21
CWM125BSNL	No Lead brass	4 3/4"	\$ 132.21
11/4" NO LEAD Bra	ass Cross for FLEXC	ON "Flex-Lite"	, WELLMATE tanks
30/50 or 40/60 Pr	essure Switch.		NO LEAD
Brass Nipple.			(Pb) < 0.25% Pb
100lb. NO LEAD Bra	ass Pressure Gau	ge.	by weighted average
3/4" NO LEAD Bras	s Relief Valve.		
3/4" NO LEAD Bras	ss No Kink Boiler I	Orain	
	CWM125BSNL L1/4" NO LEAD Bra B0/50 or 40/60 Pr Brass Nipple. LOOIb. NO LEAD Bra B/4" NO LEAD Bras	CWM125BSNL No Lead brass L1/4" NO LEAD Brass Cross for FLEXCBO/50 or 40/60 Pressure Switch. Brass Nipple. LOOIb. NO LEAD Brass Pressure Gaugh/4" NO LEAD Brass Relief Valve.	CWM125BSNL No Lead brass 4 3/4" L1/4" NO LEAD Brass Cross for FLEXCON "Flex-Lite" B0/50 or 40/60 Pressure Switch. Brass Nipple. L00lb. NO LEAD Brass Pressure Gauge.



IPWM125SSNL	CWM125SS	Stainless Steel	4 3/4"	\$ 194.47
• CWM125SS		s Steel Cross for FLEX	,	', WELLMATE tanks
• 9013FSG2 30/50	Pressure Switch	٦.		NO LEAD
• SS80-1/4 x 3	Stainless Steel	Nipple.		(Pb) < 0.25% Pb
• EIPG1002-4LNL	100lb. NO LEAD	D Brass Pressure Gau	ıge.	average
• IRV75SS	3/4" Stainless	Steel Relief Valve.		
• IHBB75SS	3/4" Stainless	Steel Hose bibb		
• HTST60-1/2SS	1/2" x 60" Stai	nless Steel PTFE Tap	е	



www.americangranby.com

In the United States: Phone (800) 776-2266 Fax (800) 729-3299
In Canada: Phone (800) 268-7570 Fax (905) 629-3204

12/4/18