

Powered by the exclusive iQ Blower System" with GPS Technology for the quietest, most energy efficient and fastest smoke & odor removal available in a range hood, external blowers offered separately

LED lighting has an extremely long lifespan; lamps may never need replacement

Mesh lined Hi-Flow™ baffle filters and removable grease rail provide supreme grease capture Works with optional Universal Make-Up Air Dampers, sold separately

#### Model Numbers:

CP55IQ369SB CP55IQ429SB

CP5/IQ1602SE CP57IQT662SE CP57E362SB

CD57E402CB



Integrated electronic controls include delay-off to continue ventilation after cooking and filter clean reminder to keep the kitchen smelling fresh.



LED lighting produces beautiful bright, clean light using minimal energy.



Hi-Flow<sup>™</sup> baffle filters for excellent ventilation efficiency.



Shown: CP57IQT482SB

# **Hood Sizes**

iQ Blower Widths 36", 42", 48" in 19.25" depth 48", 54", 60", 66", in 22.5" depth

External Blower Widths 36", 48", 60" in 22.5" depth

External blower widths 30 , 40 , 00 in 22.3 depth		
Finish		
Stocked	Brushed Stainless Steel	
Special Order	Not Available	
Features		
Light Type	LED 6-watts	
Number of Lamps	2 on 36", 42" and 48" 4 on 54", 60" and 66"	
Lighting Levels	1	
Lighting Lamps Included	Yes	
Control Type	3-Speed, Plus Boost Electronic	
Control Features	Heat Sentry™, Delay Off, Filter Clean Reminder	
Control Remote	ACR2 optional	
Filter: Standard	Stainless Steel Mesh Lined Hi-Flow™ Baffle	
Filter: Options	Not Available	
Non-ducted Capability	Yes for CP55	

### **Blower Options**

Internal	iQ6		iQ12		
Blower CFM	600		1200		
Sones High/Low	<0.3/8.5		<0.3/10	<0.3/10.0	
External In-line	ILB3	ILB6	ILB9	ILB11	
Max CFM	280	600	800	1100	
Sone levels are typically half of comparable CFM internal blowers.					
External Exterior	EB6	EB9	EB12	EB15	
Max CFM	600	900	1200	1500	
Sone levels are typically half of comparable CFM internal blowers.					

## Accessories


Universal MUA Damper	MD6TU, MD8TU, MD10TU
Non-Duct Kit	ANKCP55, for CP55 only
Non-duct Filter	AFCROUND2 for CP55


# **Installation Requirements**


Amps @ 120V: Internal Blower	CP55IQ: 4.7A, CP57IQT: 8.3A
Amps @ 120V: External Blower	CP57E: 7.0A
Electrical Connection	Direct Wire
Duct Size: Internal Blower	iQ6: 8", iQ12: 10"

Duct Size: External Blower 10"
Duct Direction Vertical
Backdraft Damper Included










only the 46-3/8" width is available in both depths



A.Installation height above the cooking surface 24–30"

B.The distance from bottom of range hood to top of range hood: 11"



