ProPEX lead-free (LF) brass CPVC socket adapters

Uponor

Submittal information

| Date submitted: | |
|---------------------------------|-----------------|
| Project Information | |
| Job name : | Location : |
| Engineer : | Date submitted: |
| Contractor : | Submitted by: |
| Manufacturer's representative : | Approved by : |
| Technical Data | |
| Material LF Brass | |

| 200°F (93°C) at 80 psi (5.5 bar) |
|----------------------------------|
| |

Product information and application use

Temp./pressure ratings

ProPEX® Lead-free (LF) Brass CPVC Socket Adapters transition Uponor PEX tubing to CPVC copper tube size (CTS) pipe for use in hot and cold domestic potable water systems and hydronic radiant heating and cooling systems.

73°F (23°C) at 160 psi (11 bar)

180°F (82°C) at 100 psi (6.9 bar)



| Part name | Part no. | A [inch] | B [inch] | C [inch] | D [inch] | E [inch] | F [inch] | G [inch] | H [inch] | Weight per UOM [lbs/UOM] | End type 1 |
|--|-----------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|-------------|--------------------------------|------------------|
| ProPEX LF Brass x CPVC Socket Adapter, 1 1/4" PEX x 1 1/4" CPVC (CTS) | CP4511313 | 3.685 | 1.12 | 1.12 | 1.385 | 1.055 | 2.11 | 0.693 | 1.445 | 0.62 | ProPEX 1-1/4" |
| ProPEX LF Brass x CPVC Socket Adapter, 1 1/2" PEX x 1 1/2" CPVC (CTS) | CP4511515 | 4.184 | 1.16 | 1.32 | 1.64 | 1.2 | 2.4 | 0.82 | 1.704 | 0.77 | ProPEX 1-1/2" |
| ProPEX LF Brass x CPVC Socket Adapter, 2" PEX x 2" CPVC (CTS) | CP4512020 | 5.227 | 1.36 | 1.72 | 2.141 | 1.5 | 3.0 | 1.07 | 2.147 | 1.42 | ProPEX 2" |

| Part name | Part no. | End type 2 |
|---|-----------|-------------|
| ProPEX LF Brass x CPVC Socket Adapter, 1 1/4" PEX x 1 1/4" CPVC (CTS) | CP4511313 | CPVC 1-1/4" |
| ProPEX LF Brass x CPVC Socket Adapter, 1 1/2" PEX x 1 1/2" CPVC (CTS) | CP4511515 | CPVC 1-1/2" |
| ProPEX LF Brass x CPVC Socket Adapter, 2" PEX x 2" CPVC (CTS) | CP4512020 | CPVC 2" |

| Installation | Related applications |
|--|-------------------------------------|
| Use the appropriate Uponor ProPEX Ring for the tubing (sold separately). Refer to the Uponor AquaPEX® Professional Plumbing Installation Guide or Uponor Radiant Floor Heating Installation Handbook for additional information. Follow all CPVC instructions and guidelines for proper CPVC | PEX-a Plumbing Systems |
| | Radiant Heating and Cooling Systems |
| | Permafrost Protection Systems |
| connections. | Turf Conditioning Systems |

| Codes | Standards | Listings |
|--|---|--|
| UPC IBC IRC IPC NPC of Canada UMC NSPC IMC | NSF-372 ASTM F877 ASTM F1960 CSA B137.5 ASTM D2846 NSF-61 NSF-14 | IAPMO-ES HUD MR 1269 ICC-ES-PMG cNSFus-pw- G U.P.Code cQAlus P321 |
| | | |

| I rademark Information | Contact information | | | |
|--|------------------------|-------------------------|--|--|
| | Uponor Inc. | Uponor Ltd. | | |
| | 5925 148th Street West | 6510 Kennedy Road | | |
| ProPEX® is a registered trademark of Uponor Inc. ProPEX [™] is a trademark of Uponor Ltd. | Apple Valley, MN 55124 | Mississauga, ON L5T 2X4 | | |
| | T 800.321.4739 | T 888.594.7726 | | |
| | F 952.891.2008 | F 800.636.9517 | | |
| | | | | |