

Features

- Single-function handshower with flow control.
- Button activated flow rate of 1.5 gal/min (5.7 l/min) to 2.0 gal/min (7.6 l/min).
- Easy to clean MasterClean™ spray nozzles.
- Air-induction technology maximizes the air/water mix for a powerful, even flow.
- 3-9/16" (90 mm) diameter sprayface.
- Includes check valve for backflow prevention.
- G1/2"-14 inlet connection.
- Earns Water Efficiency points in the LEED Green Building Rating System™ for 1.75 gal/min (6.6 l/min).

Required Accessories

K- 8593 72" Shower Hose

or

K- 9514 60" Shower Hose

or

K- 45981 Shower Hose

or

K- 45982 Shower Hose




Codes/Standards

ASME A112.18.1/CSA B125.1

EPA WaterSense®

KOHLER® Faucet Lifetime Limited Warranty

See website for detailed warranty information.



Technical Information

All product dimensions are nominal.

Handshower:

Rated maximum flow: 2 gal/min (7.6 l/min)

Notes

Install this product according to the installation guide.

Plumbing codes require approved backflow prevention devices to be installed in-line to handshowers. Please consult with local plumbing officials.

NOTICE: Choose an automatic compensating valve with the appropriate minimum flow rating to ensure your valve will provide safety at the lowest flow rates. For a handshower rated at 1.5 gal/min (5.7 l/min) maximum, use with an automatic compensating valve rated at 1.2 gal/min (4.5 l/min) or less.