ProPEX lead-free (LF) brass ice maker valves (angle)

uponor

Submittal information

Date submitted:	
Project Information	
Job name :	Location :
Engineer :	Date submitted:
Contractor :	Submitted by:
Manufacturer's representative :	Approved by :
Technical Data	

End type 1	ProPEX 1/2"		в — — — — — — — — — — — — — — — — — — —
End type 2	Compression 1/4"	4	
Temp./pressure ratings	73°F (23°C) at 160 psi (11 bar)		
	180°F (82°C) at 100 psi (6.9 bar)		
	200°F (93°C) at 80 psi (5.5 bar)		
roduct information and app	lication use		
	(LF) Brass Ice Maker Valve connects $1\!\!\!/_2$ " Uponor AquaPEX® tubing to quarter-turn and shut-off capability.	A Î	
			<u>↓</u>

Part name		Part no.	A [inch]	B [inch]	C [inch]	D [inch]	E [inch]	F [inch]	Weight per UOM [lbs/UOM]
ProPEX LF Brass Ice Maker Valve, (angle)	1/2" PEX x 1/4" O.D. LF	-4785025	2.146	2.044	0.8	0.709	0.4	0.4	0.3

Installation	Related applications
Install valves according to local building code. Do not dismantle. Refer to the Uponor Professional Plumbing Installation Guide for additional information.	PEX-a Plumbing Systems

Codes	Standards	Listings
UPC IPC NPC of Canada NSPC	ASTM F1960 CSA B125 CSA B137.5 NSF-61 NSF-372 ASME A112.18.1 ASTM F877	cCSAus
Trademark Information		Contact information

	Uponor Inc.	Uponor Ltd.
	5925 148th Street West	6510 Kennedy Road
ProPEX® is a registered trademark of Uponor Inc. ProPEX™ is a trademark of Uponor Ltd.	Apple Valley, MN 55124	Mississauga, ON L5T 2X4
	T 800.321.4739	T 888.594.7726
	F 952.891.2008	F 800.636.9517