

SPECIFICATIONS

FIGURE 2WK - 2WCL
SANITARY STAINLESS FITTINGS



304 & 316L STAINLESS STEEL SHORT ELBOWS

Butt weld fittings are used in industries that require hygienic, smooth, and crevice-free connections to ensure product purity and prevent contamination. These fittings are commonly made of stainless steel and are welded directly to tubing or piping systems to create a seamless, clean-in-place (CIP) process.

These sanitary fittings are widely used in sanitary processing systems where cleanliness, reliability, and long-term durability are critical.

FEATURES

- 304 & 316L available
- Polished ID & OD
- Manufactured from ASTM A-270 stainless steel tubing

PRODUCT SPECIFICATIONS

- Complies with 3-A standards



FIGURE NUMBER MATRIX

FNW 2WK		
Grade	Size (in.)	
304 = 74 316L = 76	1/2 = D*	2-1/2 = L
	3/4 = F*	3 = M
	1 = G	4 = P
	1-1/2 = J	6 = U
	2 = K	8 = X
*not available in 304		

FIGURE NUMBER MATRIX

FNW 2WCL		
Grade	Size (in.)	
304 = 74 316L = 76	1/2 = D*	2-1/2 = L
	3/4 = F*	3 = M
	1 = G	4 = P
	1-1/2 = J	6 = U
	2 = K	
*not available in 304		


FIGURE 2WK - 2WCL
SANITARY STAINLESS FITTINGS



304 & 316L STAINLESS STEEL SHORT ELBOWS

2WK - 45° BUTT WELD SHORT ELBOW

Tube OD (in.)	Item #		A (in.)	R (in.)	Nominal Wall	Weight (lbs)
	304	316L				
1/2	—	FNW2WK76D	0.466	1.125	0.065	0.044
3/4	—	FNW2WK76F	0.466	1.125	0.065	0.044
1	FNW2WK74G	FNW2WK76G	0.625	1.500	0.065	0.066
1-1/2	FNW2WK74J	FNW2WK76J	0.937	2.250	0.065	0.154
2	FNW2WK74K	FNW2WK76K	1.250	3.000	0.065	0.242
2-1/2	FNW2WK74L	FNW2WK76L	1.562	3.750	0.065	0.418
3	FNW2WK74M	FNW2WK76M	1.875	4.500	0.065	0.594
4	FNW2WK74P	FNW2WK76P	2.500	6.000	0.083	1.408
6	FNW2WK74U	FNW2WK76U	—	—	—	—
8	FNW2WK74X	FNW2WK76X	—	—	—	—



2WCL - 90° BUTT WELD SHORT ELBOW

Tube OD (in.)	Item #		A (in.)	Nominal Wall	Weight (lbs)
	304	316L			
1/2	—	FNW2WCL76D	1.125	0.065	0.044
3/4	—	FNW2WCL76F	1.125	0.065	0.088
1	FNW2WCL74G	FNW2WCL76G	1.500	0.065	0.132
1-1/2	FNW2WCL74J	FNW2WCL76J	2.250	0.065	0.308
2	FNW2WCL74K	FNW2WCL76K	3.000	0.065	0.528
2-1/2	FNW2WCL74L	FNW2WCL76L	3.750	0.065	0.836
3	FNW2WCL74M	FNW2WCL76M	4.500	0.065	1.276
4	FNW2WCL74P	FNW2WCL76P	6.000	0.083	2.860
6	FNW2WCL74U	FNW2WCL76U	9.000	0.109	8.184

