



Schedule 40 Fittings Technical


Schedule 40 Fittings Dimensions & Information

Wye

(Continued)

Socket x Socket x Socket

1/2" - 2" - 235 psi Maximum Internal Pressure
Rating @ 73°F (23°C) 2-1/2" - 6" - 150 psi
Maximum Internal Pressure Rating @ 73°F (23°C)
8" - Larger & All Fabricated Sizes- 100 psi
Maximum Internal Pressure Rating @ 73°F (23°C)



Part Number	Size	G	G1	G2	H	H1	H2	L	M	M1	Approx. Wt. (Lbs.)
475-120F ^{2*}	12	7- 5/16	20- 1/16	20- 1/16	13- 9/16	26- 5/16	26- 5/16	39- 7/8	13- 9/16	13- 9/16	64.53
475-140F ^{2*}	14	7- 3/16	21- 3/16	21- 3/16	14- 3/16	28- 3/16	28- 3/16	42- 3/8	14- 7/8	14- 7/8	90.24
475-160F ^{2*}	16	8- 3/4	24- 3/4	24- 3/4	16- 3/4	32- 3/4	32- 3/4	49- 1/2	17	17	122.99
475-180F ^{2*}	18	9- 7/16	27- 7/16	27- 7/16	18- 7/16	36- 7/16	36- 7/16	54- 7/8	19- 1/8	19- 1/8	165.52
475-200F ^{2*}	20	11- 7/16	30- 5/16	30- 5/16	21- 7/16	40- 5/16	40- 5/16	61- 3/4	21- 3/16	21- 3/16	216.85
475-240F ^{2*}	24	11	35	35	23	47	47	70	25- 3/8	25- 3/8	327.00


>² Fiberglass reinforced.

* Fabricated

Wye - Reducing

Socket x Socket x Socket

1/2" - 2" - 235 psi Maximum Internal Pressure
Rating @ 73°F (23°C) 2-1/2" - 6" - 150 psi
Maximum Internal Pressure Rating @ 73°F (23°C)
8" - Larger & All Fabricated Sizes - 100 psi
Maximum Internal Pressure Rating @ 73°F (23°C)



Part Number	Size	G	G1	G2	H	H1	H2	L	M	M1	Approx. Wt. (Lbs.)
475-101 ¹	3/4X1/2	5/16	2- 5/32	1- 3/8	1- 5/16	2-15/16	2- 3/8	3-11/16	1- 3/8	1- 3/8	.20
475-131 ¹	1X3/4	11/32	2	1- 3/4	1-15/32	3- 9/32	2- 7/8	4-11/32	1-23/32	1-23/32	.26
475-167 ¹	1-1/4X3/4	3/8	2- 3/4	2- 1/4	1- 5/8	3- 3/4	3- 1/2	5- 1/8	2- 1/16	2- 1/16	.61
475-168 ¹	1-1/4X1	3/8	2- 5/8	2- 1/4	1- 5/8	3- 3/4	3- 1/2	5- 1/8	2- 1/16	2- 1/16	.56
475-210 ¹	1-1/2X3/4	1/2	3- 1/2	2- 9/16	1- 7/8	4- 1/2	3-15/16	5-13/16	2-11/32	2-11/32	.58
475-211 ¹	1-1/2X1	1/2	3	2- 9/16	1- 7/8	4- 5/32	3-15/16	5-13/16	2-11/32	2-11/32	.58
475-212 ¹	1-1/2X1-1/4	1/2	3- 1/4	2- 9/16	1- 7/8	4- 1/2	3-15/16	5-13/16	2-11/32	2-11/32	.52
475-248 ¹	2X3/4	5/8	4- 1/4	3- 1/4	2- 1/8	5- 1/8	4- 3/4	6- 7/8	2- 7/8	2- 7/8	.85
475-249 ¹	2X1	15/32	4- 3/32	3-11/32	2	5- 1/8	4- 7/8	6- 7/8	2- 7/8	2- 7/8	.86
475-251 ¹	2X1-1/2	19/32	3- 7/16	3- 7/32	2- 1/8	4- 7/8	4- 3/4	6- 7/8	2- 7/8	2- 7/8	.82
475-292 ¹	2-1/2X2	1	5- 9/16	4- 1/2	3	6-15/16	6- 1/2	9- 9/16	4- 3/16	4- 3/16	3.22
475-335 ¹	3X1	11/16	5- 7/8	4- 7/32	2- 9/16	6-15/16	6- 1/8	8-23/32	4- 3/16	4- 3/16	2.49
475-336 ¹	3X1-1/4	7/8	5- 3/4	4- 1/8	2- 3/4	7	6	8- 3/4	4- 3/16	4- 3/16	2.49
475-337 ¹	3X1-1/2	1- 1/16	5-19/32	4-19/32	2-15/16	6-29/32	6-15/32	9-13/32	4	4	2.48
475-338 ¹	3X2	3/4	5- 9/16	4- 1/4	2- 5/8	6-15/16	6- 1/8	8- 3/4	4- 3/16	4- 3/16	2.47
475-339 ¹	3X2-1/2	7/8	4- 1/8	4-21/32	2- 3/4	6- 3/4	6	8- 3/4	4- 3/16	4- 3/16	2.37
475-420	4X2	1/8	4-13/16	4- 5/16	1- 7/8	6- 3/16	6- 5/16	8- 3/16	5- 1/32	2-23/32	1.98
475-422 ¹	4X3	5/8	5- 5/16	5- 1/8	2- 5/8	7- 7/32	7- 1/8	9- 3/4	5- 1/32	4	2.66
475-488F ^{2*}	5X3	1-13/16	8-13/16	7-7/16	4-13/16	11-1/16	10-7/16	15-1/4	6-1/16	3-15/16	7.04
475-490F ^{2*}	5X4	2-13/16	9-13/16	8-7/16	5-13/16	12-1/16	11-7/16	17-1/4	6-1/16	5	8.70
475-528 ¹	6X2	1/16	8- 5/8	6- 5/8	3	10	6-11/16	12-11/16	7- 9/16	4- 3/4	9.70