

COMPASS | DESIGN ENVELOPE VARIABLE SPEED WET ROTOR CIRCULATORS | SUBMITTAL

File No: 10.65
Date: MARCH 28, 2014
Supersedes: 10.65
Date: AUGUST 01, 2013

Job: _____ Representative: _____

Ordered by: _____ Date: _____
Engineer: _____ Submitted by: _____ Date: _____
Contractor: _____ Approved by: _____ Date: _____

TECHNICAL DATA

Supply voltage: 1 × 115 V - 10%/+ 6%, 60 Hz

	MINIMUM	MAXIMUM
Amp	0.05	0.65
Watt	5	45

Motor protection: The pump requires no external motor protection.

Maximum working temperature: 230°F (110°C) maximum

Maximum working pressure: 150 psi (10 bar).

Maximum relative air humidity (rh): 95%.

Flow range: 0 - 20 USgpm (0 to 1.26 L/s)

Head range: 0 - 20.0 feet (0 to 6.09 m)

Enclosure class: Type 2

Insulation class: H

Certification: ETL listed for US and Canada (conforms to ULSTD.778 certified to CSA STD. C22.2 NO.108-01)

*NSF 372 (for stainless steel models)

INLET PRESSURE

Minimum inlet pressure in relation to liquid temperature:

LIQUID TEMPERATURE	MINIMUM INLET PRESSURE
150°F (65°C)	3.0 ft (0.91 m)
167°F (75°C)	4.4 ft (1.34 m)
194°F (90°C)	9.2 ft (2.8 m)
230°F (110°C)	36.1 ft (11.0 m)

Sound pressure level: The sound pressure level of the pump is lower than 43 dB(A).

Ambient temperature: 32°F (0°C) - 104°F (40°C)

Pumped liquids: Water or water Glycol mix.

Liquid temperature: 36°F (2°C) - 230°F (110°C)**

To avoid condensation in the control box and stator, the liquid temperature must always be higher than the ambient temperature.

AMBIENT TEMPERATURE	LIQUID TEMPERATURE	
	MIN.	MAX.
32°F (0°C)	35.6°F (2°C)	230°F (110°C)
50°F (10°C)	10°C (50°F)	230°F (110°C)
68°F (20°C)	68°F (20°C)	230°F (110°C)
86°F (30°C)	86°F (30°C)	230°F (110°C)
95°F (35°C)	95°F (35°C)	194°F (90°C)
104°F (40°C)	104°F (40°C)	176°F (80°C)

MATERIALS OF CONSTRUCTION

Pump body: Cast iron (closed systems)

Stainless steel* (open systems)

Impeller: PA66

Shaft: Ceramic

Bearings: Ceramic

Gasket material: EPDM

HARDWARE KIT

Companion flange kit (contains two (2) flanges, hardware and gaskets)

Cast iron: 0.75", 1", 1.25", 1.5"

Bronze: 0.75", 1", 1.25", 1.5"


DIMENSIONS AND WEIGHTS

STAINLESS STEEL*	A	B	C	D	E	F	G	CONNECTION TYPE & SIZE	WEIGHT
Compass 20-20 ss flange	6.50 (165)	7.08 (180)	5.75 (146)	4.00 (102)	2.00 (50)	3.25 (80)	5.31 (135)	Flange - (2) ½" dia. bolt holes	8.0 (3.6)


CAST IRON	A	B	C	D	E	F	G	CONNECTION TYPE & SIZE	WEIGHT
Compass 20-20 ci flange	6.50 (165)	7.08 (180)	5.75 (146)	4.00 (102)	2.00 (50)	3.25 (80)	5.31 (135)	Flange - (2) ½" dia. bolt holes	8.0 (3.6)

NOTE:
All dimensions are in inches (mm) and weights in lbs (kg).
*Certified <0.25 weighted average percent lead and complies with California Health and Safety Code Section 116875 (commonly known as AB 1953).
** For open systems, it is recommended that the liquid temperature be less than 150°F (65°C) to avoid precipitation of calcium.

COMPASS FLANGE



COMPASS PERFORMANCE CURVES



Lights on the display indicate the Control mode selected.

TORONTO
+1 416 755 2291

BUFFALO
+1 716 693 8813

BIRMINGHAM
+44 (0) 8444 145 145

MANCHESTER
+44 (0) 8444 145 145

BANGALORE
+91 (0) 80 4906 3555

SHANGHAI
+86 21 3756 6696