

Job Name:	
Tag#	



## Submittal Data Sheet

FTXS24LVJU / RXS24LVJU

2-Ton Wall Mounted Heat Pump System



Complete warranty details available from your local dealer or at [www.daikincomfort.com](http://www.daikincomfort.com). To receive the 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California or Quebec. *If product is installed in a commercial application, limited warranty period is 5 years.*

### Indoor Specifications

Airflow Rate (cfm)	Cooling		Heating			
	H	M	H	M		
	643	494	699	572		
	L	SL	L	SL		
	350	328	445	403		
Sound (dBA) H / M / L / SL	51 / 44 / 37 / 34		48 / 42 / 37 / 34			
Dimensions (H x W x D) (in)	13-3/8 x 41-5/16 x 9-3/4					
Weight (Lbs)	31					

### Outdoor Specifications

Compressor	Hermetically Sealed Swing Type			
Refrigerant	R-410A			
Refrigerant Oil	PVE (FVC50K)			
Airflow Rate (cfm)	Cooling		Heating	
	H	1,924	H	1,854
	L	1,624	L	1,624
Sound Power Level (dBA)	66			
Dimensions (H x W x D) (in)	30-5/16 x 35-7/16 x 12-5/8			
Weight (Lbs)	159			

### Efficiency

Cooling		Heating	
SEER	20.0	HSPF	10.6
EER	12.5	COP	3.37

### Performance

Cooling (Btu/hr)	
Rated (Min/Max)	21,400 (7,800 / 21,500)
Sensible @ AHRI	16,880
Moisture Removal gal/h	1.2
Operating Range	50°F – 115°F

Rated Cooling Conditions: Indoor: 80°F DB/67°F WB  
Outdoor: 95°F DB/75°F WB

Heating (Btu/hr)	
1:@ 47° Rated (Min/Max)	25,400 (7,800 / 25,400)
2: @ 17° Rated	16,400
3: @ 5° Max	11,340
Operating Range	5°F – 65°F

1: Rated Heating Conditions: Indoor: 70°F DB/60°F WB  
Outdoor: 47°F DB/43°F WB

2: Rated Heating Conditions: Indoor: 70°F DB/60°F WB  
Outdoor: 17°F DB/15°F WB

3: Rated Heating Conditions: Indoor: 70°F DB/60°F WB  
Outdoor: 5°F DB/5°F WB

### Electrical

	208/60/1	230/60/1
System MCA	17.50	17.50
System MFA	20	20
Compressor RLA	7.9	7.1
Outdoor fan motor FLA	.32	.32
Outdoor fan motor W	66	66
Indoor fan motor FLA	.57	.57
Indoor fan motor W	48	48

MFA: Max. fuse amps MCA: Min. circuit amps (A) FLA: Full load amps (A)

RLA: Rated load amps (A) W: Fan motor rated output (W)


### Piping

Liquid (in)	1/4
Gas (in)	5/8
Drain (in)	5/8
Max. Interunit Piping Length (ft)	98.4
Max. Interunit Height Difference (ft)	65.6
Chargeless (ft)	32.8
Additional Charge of Refrigerant (oz/ft)	.21

Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

# FTXS24LVJU Dimensional Data




Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

# RXS24LVJU Dimensional Data

**DAIKIN**



Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)

Submittal Creation Date: June 2017

Page 3 of 4

# Optional Accessories



Indoor Unit		
Included	Part Number	Description
	BRP072A43	Wireless Interface Adapter
	BRC944B2-A08	Wired Remote Controller
	BCRW901A08	Wired Remote Controller Cord - 3m
	DACA-BRCW901P10	Remote Controller Cable, Plenum Rated, 10 ft
	DACA-BRCW901P25	Remote Controller Cable, Plenum Rated, 25 ft
	DACA-TS1-1	Daikin ENVi Intelligent Thermostat Kit
	DACA-CP1-1	Inline Condensate Pump (Fits inside all Daikin wall & floor mount units)
	DACA-CP4-1	External Condensate Pump
	KRP928BB2S	Interface Adaptor for DIII-NET

Outdoor Unit		
Included	Part Number	Description
	DACA-WB-3	Powder-Coated Wall-Mounted Bracket
	KEH041A43	Drain Pan Heater RXS24LV
	KKP937A4	Drain Plug for OD Unit
	KPW945A4	Low Ambient Wind Baffle / Air Adjustment Grille (15/18/24 MBH)

Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)