Lustertone® Stainless Steel Double Bowl Top Mount Quick-Clip® Sink + Faucet Kit Model(s) DRKAD2411945LC

PRODUCT SPECIFICATIONS

Lustertone® Stainless Steel Double Bowl Top Mount Quick-Clip® Sink + Faucet Kit. Overall dimensions are 41" x 19-1/2" x 4-1/2". Sink is manufactured from 18 gauge 304 Stainless Steel with a Lustrous Highlighted Satin finish, Full spray sides and bottom.


Installation Type:	Top Mount
Material:	304 Stainless Steel
Finish:	Lustrous Highlighted Satin
Gauge:	18
Sound Deadening:	Full spray sides and bottom
Number of Bowls:	2
Sink Dimensions:	41" x 19-1/2" x 4-1/2"
Bowl 1 Dimensions:	10" x 14" x 3-1/2"
Bowl 2 Dimensions:	19" x 16" x 4-3/8"
Drain Size:	2" (51mm), 3-1/2" (89mm)
Minimum Cabinet Size:	42"
Mounting Hardware:	Part # 64090008 included for
	countertops up to 3/4" (19mm) thick
Cutout Template #:	<u>1000001837</u>
	1000001836

Template is available for download at elkay.com




This sink is compliant to ADA and ANSI/ICC A117.1 accessibility requirements when installed according to the requirements outlined in these standards.

Installation Profile:



OPTIONAL ACCESSORIES

Hardware:	LK364, LK463 (2 Required)
Sinkmate:	LKSM17, LKSMHOOK,
	LKSMSPONGE, LKSMHSL





Included with Product: One LKD2439C faucet,

> one LK1141A bubbler, one LK35 strainer, one LK8 drain fitting

AMERICAN PRIDE. A LIFETIME TRADITION. Like your family, the Elkay family has values and traditions that endure. For almost a century, Elkay has been a family-owned and operated company, providing thousands of jobs that support our families and communities.

Product Compliance: ADA

BUY AMERICAN ACT

ASME A112.19.3/CSA B45.4

Faucet: ASME A112.18.1/CSA B125.1

NSF 372 (lead free)


NSF 61

ASME A112.18.2/CSA B125.2 Accessory:

Clean and Care Manual (PDF) Installation Instructions (PDF) Limited Lifetime Warranty (PDF)

Similar models are available with: additional ADA depths

Three Faucet Holes 1-1/2" (38mm) Diameter Faucet Holes on 4" (102mm) Centers One Slotted Hole 1-1/8" (29mm) Diameter Slotted Hole



In keeping with our policy of continuing product improvement, Elkay reserves the right to change product specifications without notice. Please visit elkay.com for the most current version of Elkay product specification sheets. This specification describes an Elkay product with design, quality, and functional benefits to the user. When making a comparison of other producers' offerings, be certain these features are not overlooked.