



MATERIAL & STYLE

Polyethylene Blend
Black Exterior
White Interior
Flared Wall
Wall Thickness: 0.50"

1118-12

13 lbs

1118-26

25 lbs

OPTIONS

Mouseholes: 2

	A	B	C	D	E
1118-12	13 3/4"	20 1/2"	12"	19 1/4"	25 1/2"
1118-26	13 3/4"	20 1/2"	26"	19 1/4"	25 1/2"



MEDIUM DUTY

For use in non-vehicular traffic situations only. Weights and dimensions may vary slightly. Actual load rating is determined by the box and cover combination.

© 2019 Oldcastle Infrastructure, Inc



OPTIONS



Available Covers:

- Composite, Flush Solid
- Composite, Flush with Cast Iron Reader Door
- Composite, Flush with AMR Recess
- Composite, Flush with AMR Bracket
- Polymer, Flush Solid
- Polymer, Flush with Cast Iron Reader Door
- Ductile Iron, Flush Solid
- Ductile Iron, Flush with Max View Reader Door

Add On Options:

- Touch Read Hole

RAW MATERIAL SPECIFICATION

BODY : Material Property

Density, g/ cm³
Tensile Strength, at break
Flexural Modulus
Chemical Resistance
Water Absorption
UV Resistance

Test Method

ASTM D1505
ASTM D638
ASTM D790
ASTM D543
ASTM D570
ASTM G154

Typical Value¹

0.90 minimum
≥ 3,000 psi
120,000 min, not to exceed 240,000 psi
Retention of 75% of physical properties, less than 2% weight change
Retention of 75% of physical properties, less than 2% weight change
Retention of 75% of physical properties after 2160 hrs, less than 2% weight change

¹ The values listed for physical property measurements are nominal values only. Certain physical property measurements are subject to variations consistent with the test methods and are within a generally accepted range for such values.

! WARNING: Cancer - www.P65Warnings.ca.gov

All information contained on this sheet is current at the time of publication.
Oldcastle reserves the right to discontinue or update product information without notice.

Revision 10/30/19
© 2019 Oldcastle Infrastructure, Inc