

FEATURES & SPECIFICATIONS

INTENDED USE

Provides general illumination in residential applications. Ideal for use in closets, foyers, hallways, corridors, bedrooms, offices, utility work areas, stairways and more. **If required for commercial applications or operation more than eight (8) hours per day, select a commercial-rated flush mount.**

CONSTRUCTION

Features a white acrylic diffuser with a defined outer edge. Diffuser twist-locks into housing for a hardware-free appearance and provides easy access for cleaning.

OPTICS

Produces 2040 lumens at 50,000 hours life. LEDs rated for 50,000 hours of use, LED driver rated for 30,000 hours of use.

ELECTRICAL

Fixture operates at 120 volts, 60 Hz. Standard input = 30 watts, 68 lumens per watt.

Works with most standard incandescent dimmers (see list of approved dimmers).

INSTALLATION

All mounting hardware included.

LISTINGS

UL Certified to US and Canadian standards and listed suitable for damp locations. Some items ENERGY STAR® certified

WARRANTY

5-year limited warranty. Complete warranty terms located at: www.acuitybrands.com/support/customer-support/terms-and-conditions

NOTE: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25°C. Specifications subject to change without notice.

Catalog Number
Notes
Type

Decorative Indoor

Hildon Residential LED Flush Mount

HIGH-PERFORMANCE LED



Specifications

Height: 3-3/16 (8.1)

Diameter: 14 (35.6)

Weight: 2.1 lbs

All dimensions are inches (centimeters) unless otherwise indicated.

ORDERING INFORMATION

For shortest lead times, configure product using **bolded options**.

Example: FMHLDL 14 20840

Series	Module/CRI	Color temperature
FMHLDL 14 ¹ 14 Hildon LED flush mount, 14"	208 >80CRI	40 4000 K 30 3000 K



Notes

¹ FMHLDL 14 20830 is not ENERGY STAR® certified

Replacement Parts: Order as separate catalog number.	
DFMHLDL 14	14" Hildon acrylic diffuser

LED Hildon Flush Mount

LIGHTING FACTS



SUGGESTED DIMMERS	
The FMHLDL is designed to operate with most standard Triac Based dimmers and is not compatible with 0-10v dimming systems. The following is a list of dimmers tested and does not imply any guarantee or warranty of compatibility with a particular application. Unlisted dimmers do not imply non-compatibility.	
Manufacturer	Part number(s)
Lutron	CT-600P/CT-603P
	DV-600P/DV-603P
	CTCL-153P
	DVCL-153P
	AYCL-153P
Leviton	DVELV-300P
	R50-IPL06
Pass & Seymour	6615-P
	HCL453PTCCCV6