

|                |
|----------------|
| Catalog Number |
| Notes          |
| Type           |

## FEATURES & SPECIFICATIONS

**INTENDED USE** — Provides general illumination in residential and light commercial applications. Ideal for use in workshops, utility rooms and garages.

**ATTRIBUTES** — Slim, compact design available in 1- or 2- lamp configurations. Quality, postpainted steel construction.

MNS5 fixture ship standard with low-power factor magnetic ballast (120 volt, 60Hz).

MNS5 fixtures ship with 3000K linear fluorescent lamps. MNS8 fixtures are not available lamped.

MNS8 fixtures ship with normal power factor residential ballast (120 volt, 60 Hz) ensures no flickering and quiet operation. For use with non-dimmable switches only.

**LISTINGS** — CUL listed to US and Canadian safety standards and suitable for damp locations.

**WARRANTY** — 1-year limited warranty. Complete warranty terms located at:

[www.acuitybrands.com/support/warranty/terms-and-conditions](http://www.acuitybrands.com/support/warranty/terms-and-conditions)

**Note:** Actual performance may differ as a result of end-user environment and application.

Specifications subject to change without notice.

# Fluorescent Mini-Strip T5 or T8 Striplight



## ORDERING INFORMATION

| Item    | Catalog number      | UPC          | Description   | # of lamps | Length          | Width        | Height       | Wattage | Lamp type | Lamp include | Pallet Quantity | Standard Carton Quantity |
|---------|---------------------|--------------|---------------|------------|-----------------|--------------|--------------|---------|-----------|--------------|-----------------|--------------------------|
| *138RLL | MNS5 1 21 LP M6     | 745973907375 | T5 mini-strip | 1          | 34-3/4" (88.3)  | 1-1/2" (3.8) | 2-1/8" (5.4) | 21      | T5        | Y            | 270             | 1                        |
| *138RLM | MNS5 1 28 LP M6     | 745973907382 | T5 mini-strip | 1          | 46-3/4" (118.7) | 1-1/2" (3.8) | 2-1/8" (5.4) | 28      | T5        | Y            | 240             | 1                        |
| *138RLP | MNS5 2 21 LP M6     | 745973907443 | T5 mini-strip | 2          | 34-3/4" (88.3)  | 1-3/4" (4.4) | 2-3/8" (6)   | 21      | T5        | Y            | 270             | 1                        |
| *138RLR | MNS5 2 28 LP M6     | 745973907566 | T5 mini-strip | 2          | 46-3/4" (118.7) | 1-3/4" (4.4) | 2-3/8" (6)   | 28      | T5        | Y            | 240             | 1                        |
| *226NEP | MNS8 1 17 120 RE M6 | 888791209297 | T8 mini-strip | 1          | 24-3/8" (61.9)  | 1-5/8" (4.1) | 2-3/4" (7)   | 17      | T8        | N            | 448             | 1                        |
| *204RUG | MNS8 1 25 120 RE    | 745977729386 | T8 mini-strip | 1          | 36-3/8" (92.4)  | 1-5/8" (4.1) | 2-3/4" (7)   | 25      | T8        | N            | 192             | 1                        |
| *204RUH | MNS8 1 32 120 RE M6 | 745977729430 | T8 mini-strip | 1          | 48-3/8" (122.9) | 1-5/8" (4.1) | 2-3/4" (7)   | 32      | T8        | N            | 168             | 1                        |
| *208GJ1 | MNS8 2 17 120 RE    | 784231542323 | T8 mini-strip | 2          | 24-3/8" (61.9)  | 2-3/8" (6)   | 2-7/8" (7.3) | 17      | T8        | N            | 448             | 1                        |
| *208GHV | MNS8 2 25 120 RE    | 784231542286 | T8 mini-strip | 2          | 36-3/8" (92.4)  | 2-3/8" (6)   | 2-7/8" (7.3) | 25      | T8        | N            | 192             | 1                        |
| *204RUJ | MNS8 2 32 120 RE M6 | 745977729690 | T8 mini-strip | 2          | 48-3/8" (122.9) | 2-3/8" (6)   | 2-7/8" (7.3) | 32      | T8        | N            | 168             | 1                        |

### MNS5 and MNS8 Mounting Hole Dimensions

