

NITROGEN REGULATORS

PART NO.	MAXIMUM OUTLET PRESSURE	GAS	OUTLET FITTING
EN-450F	450 PSIG	Nitrogen	1/4" Flare Male
EN-650F	650 PSIG	Nitrogen	1/4" Flare Male
EN-850F	850 PSIG	Nitrogen	1/4" Flare Male

Heavy duty regulators that deliver the pressure and volume most requested by professionals.



FM-100F (shown)

NITROGEN FLOWMETER

Ideal for HVAC and refrigeration brazing or purging applications. Brazing without nitrogen causes internal oxidation scale that can flake off and damage the parts inside a system. Brazing with nitrogen flowing through system displaces oxygen and eliminates internal scale.

- Visually confirms gas is flowing through system while brazing
- Saves gas by delivering precise flow of nitrogen into system
- Solid brass body and fittings with visible round chromium steel bar
- Inlet and outlet connections use standard 1/4" flare (7/16"-20) fittings
- Set regulator to 50 PSI and adjust flowmeter range from 0-75 SCFH
- Auto-Reset safety protects from regulator over-pressure delivery



NITROGEN PURGE & BLOW GUN KIT

- 6 ft. / 1.8m Hose (H72Y)
- EN-450F High Pressure Regulator
- Quality Die-cast Blow Gun (BG-1)
- Multiple Uses: Purges, Blow, Leak Tests
- Add Stands to KPN-1 Kit:
 - KPN-20S Includes Blow Gun Kit and Stand for 20 Cubic ft. Cylinders
 - KPN-40S Includes Blow Gun Kit and Stand for 40 Cubic ft. Cylinders



KPN-1
Blow gun kit



NITROGEN ACCESSORIES

NITROGEN CYLINDER STAND

Carry cylinders easily. These all steel stands are made for rugged use. Weighs only 4 lbs.

- **C-920 Stand**
Holds 20 cu. ft. nitrogen cylinder.
- **C-940 Stand**
Holds 40 cu. ft. nitrogen cylinder or 10 lb. CO2 cylinder.
- **C-940CW Cart**
Same as C-940, but with wheels and handle.

REFRIGERANT HOSE

- Nylon Lined/Low Porosity
- UL Listed
- Suitable for R12, R13A, R22, R500, R502, R410A and HCFC Blends
- 6 ft. Long

H72Y



BLOW GUN

- OSHA Approved Nozzle
- Durable Construction
- ON/OFF Lever

BG-1

