

HEAT/COOL ROOM AIR CONDITIONERS

Electric Heat (AE093G35AX, AE123G35AX, AE183G35AX) or
Heat Pump (AH093G35AX, AH123G35AX, AH183G35AX) Models

Wise Decision.
It's an Amana[®] brand.



- **Electronic touch pad with remote control**
- **High energy efficiency** with models up to 10.9 CEER saving you money when compared to lower CEER models.
- **Solid bottoms on outercases** for full seal – thru-the-wall installation.
- **100% full factory run test** on all units for high reliability and dependability.
- **Ball bearing fan motors** that are reliable, start quickly and run quietly.
- **Multi-directional airflow** to allow for cooling or heating to any part of the room. Some models contain automatic 2-way air swing feature.
- **Easy access slide-out filter** (left or right side pullout) – has a permanent polypropylene filter mesh that is easy to remove and clean.
- **Hydrophilic coating on evaporator and condenser Coils** on ALL models which allows better moisture removal, increased air flow, increased heat exchange, higher efficiencies and longer compressor life than units with uncoated coils.
- **Condensate drain spouts** on ALL models to direct condensate drainage.
- **LCDI power cords** to help reduce crimping or cuts on power cords.

Amana Models	Electric Heat Models			Heat Pump Models		
	AE093G35AX*	AE123G35AX*	AE183G35AX*	AH093G35AX*	AH123G35AX*	AH183G35AX*

General Features:

Voltage	230/208	230/208	230/208	230/208	230/208	230/208
Discharge Air	Top	Top	Side	Top	Top	Side
Auto Air Swing	No	No	Yes	No	No	Yes
Slide-out Filter	Side Pull-out	Side Pull-out	Front Pull-out	Side Pull-out	Side Pull-out	Front Pull-out
Approx. Chassis Wgt.	88 lbs	91 lbs	132 lbs	91 lbs	96 lbs	143 lbs
Approx. Shipping Wgt.	108 lbs	111 lbs	151 lbs	111 lbs	116 lbs	162 lbs

Cooling:

Capacity / BTUH	9,000 / 8,700	11,600 / 11,200	17,600 / 17,200	9,000 / 8,700	11,600 / 11,200	17,300 / 17,000
Amps	3.7 / 4.0	4.5 / 4.9	7.1 / 7.6	3.9 / 4.2	5.1 / 5.3	7.3 / 7.8
Watts	820 / 790	1,050 / 1,020	1,630 / 1,590	910 / 880	1,170 / 1,130	1,750 / 1,720
CFM	280	280	450	280	280	590
E.E.R.	11.0	11.0	10.8	9.9	9.9	9.9
C.E.E.R.	10.9	10.9	10.7	9.8	9.8	9.8
Dehumidification - pts/hr	2.3	2.6	4.2	2.2	2.5	4.1

Electric Heat:

Capacity / BTUH	10,700 / 8,500	10,700 / 8,500	11,000 / 9,000	10,700 / 8,500	10,700 / 8,500	11,000 / 9,000
Amps	16.0 / 14.6	16.0 / 14.6	16.0 / 15.6	16.0 / 14.6	16.0 / 14.6	16.0 / 15.6
Watts	3,580 / 2,770	3,580 / 2,770	3,680 / 3,030	3,580 / 2,770	3,580 / 2,770	3,680 / 3,030

Heat Pump: (Reverse cycle)

Capacity / BTUH	n/a	n/a	n/a	7,500 / 7,200	10,200 / 9,900	14,300 / 14,000
Amps	n/a	n/a	n/a	3.5 / 3.8	5.1 / 5.3	6.5 / 7.0
Watts	n/a	n/a	n/a	810 / 780	1,150 / 1,110	1,520 / 1,490
C.O.P	n/a	n/a	n/a	2.8 / 2.8	2.6 / 2.6	2.8 / 2.8
Thermostatic Drain Valve	n/a	n/a	n/a	Yes	Yes	Yes

Dimensions:

Outer case-sleeve						
Height	15 3/8"	15 3/8"	16 7/8"	15 3/8"	15 3/8"	16 7/8"
Width	22 5/8"	22 5/8"	26"	22 5/8"	22 5/8"	26"
Depth	24"	24"	27 3/4"	24"	24"	30 1/2"
Depth with Front	26 3/4"	26 3/4"	29 3/4"	26 3/4"	26 3/4"	32 1/2"

* All units meet or exceed 06-01-14 D.O.E. CEER Minimums

Features: (all models)

Electrical	4.0' LCDI power cord; Perpendicular plug; 20-amp circuit breaker
Agency Approval	U.L (Under Writers Laboratory) listed; USA and Canada
Chassis type	Slide-out for easy installation and service accessibility
Fan Speeds	3 speeds, High, Medium and Low
Fan ONLY	Yes - High, Medium and Low speed
Condensate drain	Yes - condensate drain spout on the wall sleeve
Window kit	Yes - included

Plug Type

Perpendicular



20 Amps
250 Volts



Call your Amana brand PTAC sales representative at **800-647-2982** for complete details.

Before purchasing this appliance, read important information about its estimated annual energy consumption, yearly operating cost, or energy efficiency rating that is available from your retailer.

www.amana-ptac.com

Our continuing commitment to quality products may mean a change in specifications without notice. © 2015 Goodman Company, L.P. Amana is a registered trademark of Maytag Corporation or its related companies and is used under license to Goodman Company, L.P., Houston, TX, USA. All rights reserved.

CB-ARAC4 01-15