


PRESS ON ACCESS DOORS (HINGE & CAM) (H)



Product Data Sheet



Description

Elgen's Press On Hinge & Cam (H) is used to provide easy access into rectangular ductwork.
Double paneled with front and back metal plates, and 1" insulation

Standard Construction

Door Panel:

Consists of 24GA GA, manufactured from ASTM A-653 G60, panels mechanically locked together.

Insulation:

1" high-density fiberglass insulation Classifications; FHC25/50, ASTM C 1071; Type 1, ASTM G 21, Greenguard Indoor Air Quality Certified*, Greenguard Children and Schools, NFPA 90A and 90B.

Gasket:

Closed-cell neoprene gasket is UL94HF1 listed with service temperature range of 20° F to 200° F The gasket is bonded to the inside of the frame.

Press-on Frame:

Measuring 6" x 6" to 12" x 12" are manufactured from 24 gauge galvanized steel. Frames measuring 14" x 14" to 24" x 24" are manufactured from 22 gauge galvanized steel.

Cams & Strikes:

The cam is stamped using 16 Ga galvanized steel. The latch is stamped from 20 Ga galvanized steel. Each cam is secured to the door with a rivet. The latch is secured to the frame in two locations for added rigidity.

Features

Meets 2005 SMACNA Standards for pressure class & gauges(Refer to page 7-2, figure 7-2)

Union Made

Regular doors can be used up to 4"wg

High Pressure doors can be used up to 10"wg

Optional Construction

Closed cell foam insulation(in place of fiberglass)

Additional Cams

1.5" thick and 2" thick

Neoprene gasket bonded outside of the frame

Stainless Steel 304

Stainless Steel 316

Aluminum

PCD

Galvanneal (Paint Grip)

Hi-Pressure (Up to 10" W.G. +/-):

20GA and Fully Welded

1/16" Diameter Galvanized Cable-wire

Locking Haps for Padlocks

Packaging

Size A x B	Flange Size	# of Cams	Box Qty	Weight (lbs)
6 x 6	1	1	48	1.3
8 x 8	1	1	20	1.9
10 x 10	1	1	20	2.7
12 x 12	1	1	16	3.6
14 x 14	1	1	5	5.5
16 x 16	1	2	5	7.2
16 x 12	1	2	5	5.8
18 x 18	1	2	4	8.8
18 x 12	1	2	4	6.4
20 x 20	1	2	4	10.5
24 x 24	1	2	4	14.5
24 x 12	1	2	4	8.2

Guarantee

All Elgen products are guaranteed by Elgen Manufacturing against defective material.

Elgen Manufacturing

10 Railroad Ave, Closter NJ 07624

Tel: 800.503.9805 :: Fax: 201.964.9030

info@elgenmfg.com :: www.elgenmfg.com