

PC 626



SPECIALTY GRADE, CAMOUFLAGE CLOTH DUCT TAPE

TYPICAL APPLICATIONS

- For sealing, waterproofing, holding, camouflaging, sound deadening, covering reflective surfaces and patching applications

PRODUCT FEATURES

- Good conformability
- Easy to unwind and tear
- Available in Army ACU digital and lusterless camouflage patterns

CONSTRUCTION

Overall Grade/Function: Specialty

Backing: Waterproof, polyethylene film with a cloth carrier

Adhesive: Natural rubber

STANDARD WIDTH(S)

48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)



ARMY DIGITAL
(CAM)



RT GREEN
(GRN)



RT BROWN
(BRN)

PHYSICAL PROPERTIES

STANDARD

METRIC

Tensile Strength

23 lbs/in width

40.3 N/10 mm

Adhesion to Stainless Steel

48 oz/in width

5.25 N/10 mm

Thickness

10 mils

0.25 mm

Elongation

20%

20%

Service Temperature Range

50 F to 200 F

10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

