

# **MODEL LD-7 WATER LEAK DETECTOR**



# **Standard Items**

- (1) Amplifier with Volume Control and Mute Switch
- (2) Sensor with 3-Point Ground Plate
- (3) Stereo Headphones

#### **Features**

- Compact amplifier (with mute switch) fits inside the palm of the user's hand. Press the mute switch (on/ off) to activate the leak sounds in the headphones, and then release the mute switch when moving the sensor (protects your hearing!).
- Designed for all of the water leak detection applications, including leak surveys and leak pinpointing. Use the 3-point ground plate for pinpointing on streets and concrete slabs. Use the magnet base or the contact rod for leak surveys at hydrants, valves, or meters.
- Extremely compact and lightweight. The entire LD-7 inside its heavy duty carrying case measures only 14 inches x 10 inches x 6 inches, small enough to be stored behind the seat inside the cab of the truck.

#### **Standard Accessories**

- (4) Magnet Base
- (5) 3-Section Contact Rod
- (6) Heavy Duty Carrying Case
- (7) Instruction Manual (not shown)

#### **Specifications**

# **Amplifier**

Input Impedance
Output Impedance
Amplification
Frequency Range
430k ohm +/- 1%
4-10 ohm
56 dB +/- 3%
100Hz to 1000Hz

Power Consumption : 2 AA dry cell batteries (1.5 V x 2)
Power Consumption : 20 mA Nominal (30-hour life)

Weight : .507 lb. (230 gm)Size : 5.7" x 1.25" x 3"

(145mm x 30mm x 68mm)

# Headphones

• Impedance : 20 ohms

(mini-stereo headphones)

# **ABS Carrying Case**

Weight (full)
 Size
 5.84 lb. (2.65 Kg)
 14" x 10" x 6"

(356mm x 254mm x 152mm)



