

**NIBCO**

1516 Middlebury Street  
Elkhart, IN 46516-4740

**Phone:** 574.295.3000 • **Fax:** 800.234.0557

**E-Mail:** [info@nibco.com](mailto:info@nibco.com) • **Web site:** [www.nibco.com](http://www.nibco.com)

## Material Number NLG100K, LD-2000 - Butterfly Valve - Ductile Iron, Lug Type, 200 PSI, Handle

The NIBCO® ductile iron lug butterfly valve provides ease of operation with quarter-turn (90 degrees) open to close. With the internal stem/disc geometric drive design, there is no need for pins or bolts that may create leak paths or turbulence in the waterway. An extended neck allows for insulation up to 2 inches. The unique molded-in EPDM seat liner with aluminum bronze disc is recommended for most water applications. Please refer to NIBCO technical data sheets, chemical resistance guides and

[+ more](#)



### Specifications

<b>UPC Code</b>	039923717801
<b>Type</b>	Butterfly Valve
<b>Connection Type</b>	L - Lug
<b>Stem Material</b>	Metal - NIBCO - Steel - Stainless
<b>Valve Size</b>	6
<b>Material</b>	Ductile Iron
<b>Disc Material</b>	Aluminum Bronze
<b>Valve Operator</b>	Lever-Lock Handle
<b>Description</b>	LD20003 6 LUG BFV L/LK HNDL DUCT IRON
<b>*eClass Classification</b>	Ductile Iron Butterfly Valves
<b>All Type of Item</b>	Valve

**Turns/Operation**

Quarter-Turn

**Weight**

25.41 lb