

## PEX-a pipe supports

### Project information

|                                 |                 |
|---------------------------------|-----------------|
| Job name :                      | Location :      |
| Engineer :                      | Date submitted: |
| Contractor :                    | Submitted by:   |
| Manufacturer's representative : | Approved by :   |

### Technical data

Prop 65 label required? No

### Product information and application use

PEX-a Pipe Support is a non-combustible, self-gripping, galvanized-steel channel for crosslinked polyethylene (PEX-a) pipe. It provides continuous, uninterrupted support of PEX-a pipe, allowing hanger placement similar to that of metallic pipe. Use PEX-a Pipe Support in conjunction with un-insulated Uponor AquaPEX® or Wirsbo hePEX™ PEX-a pipe in ASTM E84 plenum applications. The PEX-a pipe with pipe support can be insulated with typical CTS (copper tube size) pipe insulation. PEX-a Pipe Support is offered in 9-foot lengths and comes with nylon-coated, stainless-steel strapping.



| Part name                                                   | Part no.  | A [inch] | B [inch] | C [inch] | Weight per UOM [lbs/UOM] | Material group |
|-------------------------------------------------------------|-----------|----------|----------|----------|--------------------------|----------------|
| 1/2" PEX-a Pipe Support, 9-ft. length:                      | F7040500: | 108:     | 0.677:   | 0.406:   | 1.1:                     | -:             |
| 3/4" PEX-a Pipe Support, 9-ft. length:                      | F7040750: | 108:     | 0.921:   | 0.552:   | 1.5:                     | -:             |
| 1" PEX-a Pipe Support, 9-ft. length:                        | F7041000: | 108:     | 1.163:   | 0.698:   | 1.91:                    | -:             |
| 1 1/4" PEX-a Pipe Support, 9-ft. length:                    | F7041250: | 108:     | 1.396:   | 0.837:   | 2.1:                     | -:             |
| 1 1/2" PEX-a Pipe Support, 9-ft. length:                    | F7041500: | 108:     | 1.623:   | 0.973:   | 2.5:                     | -:             |
| 2" PEX-a Pipe Support, 9-ft. length:                        | F7042000: | 108:     | 2.095:   | 1.256:   | 3.6:                     | -:             |
| 2 1/2" PEX-a Pipe Support, 9-ft. length:                    | F7042500: | 108:     | 2.562:   | 1.537:   | 4.6:                     | -:             |
| ✓ 3" PEX-a Pipe Support, 9-ft. length:                      | F7043000: | 108:     | 3.024:   | 1.81:    | 6.2:                     | -:             |
| 3 1/2" PEX-a Pipe Support, 9-ft. length:                    | F7043500: | 108:     | 3.481:   | 2.088:   | 6.4:                     | -:             |
| PEX-a Pipe Support Strapping for 1/2", 3/4" and 1" PEX:     | Q7410510: | -:       | -:       | -:       | 0:                       | -:             |
| PEX-a Pipe Support Strapping for 1 1/4", 1 1/2" and 2" PEX: | Q7411220: | -:       | -:       | -:       | 0.01:                    | -:             |
| PEX-a Pipe Support Strapping for 2 1/2", 3", 3 1/2" PEX:    | Q7412540: | -:       | -:       | -:       | 0.01:                    | -:             |

### Installation

Install PEX-a Pipe Support vertically or horizontally for plenum and non-plenum applications. Refer to the Uponor PEX-a Pipe Support Instruction Sheet for installation guidelines.

### Related applications

PEX-a Plumbing Systems  
Radiant Heating and Cooling Systems  
AquaSAFE™ Fire Safety Systems

### Codes

IMC|UMC:

### Standards

ASTM E84:

### Listings

QAI P321 (up to 3"):

### Footnotes

-

### Contact information

Uponor Inc.  
5925 148th Street West  
Apple Valley, MN 55124  
T 800.321.4739  
F 952.891.2008

Uponor Ltd.  
6510 Kennedy Road  
Mississauga, ON L5T 2X4  
T 888.594.7726  
F 800.638.9517