

CL960 / CL961 TECHNICAL DATA SHEET

PENI-LUBE PENETRATING OIL

PRODUCT DESCRIPTION:

- Non-Conducting
- Lubricates
- Never Dries
- Prevents Corrosion

This heavy duty penetrant is designed to work fast. The non-conductive formula with moisture displacer, lubricates parts and never dries. Spray it on moving parts that have become stationary to loosen rust or corrosion, making it easy to separate the surfaces. Clinging foam penetrates fast to work immediately. Non-conducting up to 24,800 volts.

AREAS OF USE:

Lubricates: locks, hinges, moving parts, nuts and bolts.
Use on and in: refrigeration equipment, automobiles and workshops.

SPECS:

	CL960	CL961
Can Size:	16 oz.	20 oz.
Net Weight:	12 oz.	15 oz.
Shipping Weight:	13 lbs.	16 lbs.

UPC Numbers:

CL960 7 13014 11960 6

CL961 7 13014 11961 2

Packaged: 12 cans per case

Extender Tube: Y

REGULATORY:

Ozone Depleting Compounds: None

Recyclable Package: Yes

VOC Compliant CARB: Yes

VOC Compliant OTC: Yes

Flammability: Flammable

PHYSICAL CHARACTERISTICS:

Color: Light Brown

Fragrance: Pine/petroleum

Shelf Life: 1 year +

See label side panel for First Aid and additional Precautionary Statements

24 HOUR MEDICAL EMERGENCY NUMBER:

1-866-836-8855

KEEP OUT OF REACH OF CHILDREN
CONSULT MSDS BEFORE USING



MADE IN THE
USA

Federal regulations prohibit CFC propellants in aerosols.

